

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Permit <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Form or Lease Name	
H. T. Mattern (NCT-C)	
9. Well No.	
1 8	
10. Field and Pool, or Will not	
Drinkard	
12. County	
Lea	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - A" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator
Gulf Oil Corporation
3. Address of Operator
Box 670, Hobbs, N.M. 88240
4. Location of Well
UNIT LETTER <u>A</u> <u>660</u> FEET FROM THE <u>north</u> LINE AND <u>447</u> FEET FROM
THE <u>east</u> LINE, SECTION <u>18</u> TOWNSHIP <u>21S</u> RANGE <u>37E</u> N.M.P.M.
15. Elevation (Show whether DF, RT, GR, etc.)
3484' GL

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>
OTHER <u>Set Dynadrill to straighten hole</u> <input type="checkbox"/>			

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1503.

Drilling of 7-7/8" hole was started at 1278'. Hole was drilled to 4740'. Schlumberger directional survey indicated 14° deviation. Set plugs as follows:

#1, 35 sacks Class C Neat , 4740-4640'
#2, " 3950-3850'
#3, " 3450-3350'
#4, " 2530-2430'
#5, 350 sacks Class H with 2% CaCl2 plus 10# sand per sx plus 8# salt per sx, 2000-1700'. WOC.

Will set Dynadrill at approximately 1700' to straighten hole and re-drill from 1700' to 4740' and continue drilling operations as originally set forth on form C-101 dated 9-2-75.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED A. F. Berlin TITLE Area Engineer DATE 11-12-75

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

17. 11. 1977

RISE
10:00 A.M.