

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
B-1732	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
Gulf Oil Corporation

3. Address of Operator
Box 670, Hobbs, New Mexico 88240

4. Location of Well
UNIT LETTER A 330 FEET FROM THE North LINE AND 600 FEET FROM
THE East LINE, SECTION 16 TOWNSHIP 21-S RANGE 37-E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3465' GL

7. Unit Agreement Name
8. Farm or Lease Name Harry Leonard (NCT-E)
9. Well No. 6
10. Field and Pool, or Wildcat Drinkard
12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Capitan Drilling Company spudded 11" surface hole at 12:15 PM, January 1, 1976. Drilled to 1305'. Ran 31 joints and 1 cut joint, 1291' of 8-5/8" OD 24# K-55 ST&C casing set and cemented at 1305' with 350 sacks of Class C with 4% gel and 2% Ca Cl2 and 200 sacks of Class C with 2% Ca Cl2. Cement circulated. WOC 23 hours. Tested casing with 1100#, 30 minutes, OK.

Started drilling 7-7/8" hole at 1305' at 5:00 PM, January 3, 1976.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>D. F. Berlin</u>	TITLE <u>Area Engineer</u>	DATE <u>January 5, 1976</u>
APPROVED BY <u>Harry Sexton</u>	TITLE <u></u>	DATE <u>1976</u>
CONDITIONS OF APPROVAL, IF ANY:		