

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 12275

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal HM 12

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Hat Mesa Morrow

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 12, T-21-S, R-32-E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

1. OIL ☐ GAS ☐ ☒ OTHER

APR 28 1978

2. NAME OF OPERATOR

BELCO PETROLEUM CORPORATION

U. S. GEOLOGICAL SURVEY

3. ADDRESS OF OPERATOR

HOBBS, NEW MEXICO

10,000 Old Katy Road - Suite #100, Houston, TX 77055

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

1980' FSL, 660' FWL Section 12

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well has failed to produce in an economical manner. The well will therefore be plugged and abandoned.

Shut-in date: 4/1/78

Last production test: 4/1/78 50 Mcf in 7 hrs., 7/64" choke w/530# FTP

Recommended plugging procedure:

1. Sqz perfs @ 13,958-13,993 w/50 sx cement.
2. Circ well w/9.55 ppg mud.
3. Pull tbg & RTTS pks.
4. Run free point on 5½" csg.
5. Cut & pull 5½" csg @ deepest free point.
6. Spot 100' cmt plug 50' in, 50' out of 5½" csg cut.
7. Cut surface csg 2' below ground level.
8. Spot 5 sack cement plug @ surface.
9. Erect monument as required.
10. Restore wellsite as required.

SEE ATTACHED FOR
CONDITIONS OF APPROVAL

This plugging operation is expected to require 15 days, anticipated to occur approx.
June 1, 1978.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Administrative Geologist

DATE

4/26/78

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED
AS AMENDED

DATE

MAY 1 1978

a. a. l.

ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Drilled with Mud

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations; and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 1: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 2: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents; not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
WASHINGTON, D.C. 20240
MAY 1968

68-1010

100-1010

100-1010