

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPERATE OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT - FORM C-101, FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
2. Name of Operator Gulf Oil Corporation	5. State Oil & Gas Lease No. B-1732
3. Address of Operator Box 670, Hobbs, N.M. 88240	7. Unit Agreement Name
4. Location of Well UNIT LETTER G 2310 FEET FROM THE North LINE AND 1900 FEET FROM THE East LINE, SECTION 25 TOWNSHIP 21-S RANGE 36-E NMPM.	8. Farm or Lease Name W.A. Ramsay (NCT-B)
	9. Well No. 7
	10. Field and Pool, or Wildcat Drinkard
15. Elevation (Show whether DF, RT, GR, etc.) 3535' GL	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Reached total depth of 7-7/8" hole at 6850' at 10:15 PM, March 1, 1977. Ran 188 joints and 2 cut joints, 6834' of 5-1/2" OD 15.50# K-55 LT&C casing and set at 6850' and DV tool at 3050'. Cemented first stage with 400 sacks of lite cement and 500 sacks of Class C Neat with .5% CFR-2. Opened DV tool and cement circulated. Cemented second stage with 1250 sacks Class C with 16% gel, 2% salt and .2% HR-7 and 150 sacks of Class C Neat. Cement circulated. WOC over 24 hours. Cleaned out to 6818' and tested casing with 4,000#, 30 minutes, CK.

Installed valves above ground level off casing. Inspected by Mr. L. A. Clements. Filled cellar.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>L. T. Berlin</u>	TITLE <u>Area Engineer</u>	DATE <u>March 8, 1977</u>
APPROVED BY <u>[Signature]</u>	TITLE <u></u>	DATE <u>1977</u>
CONDITIONS OF APPOINTMENT, IF ANY:		