Set and ceme 150 sacks cl W O C over 2 Installed va by State of Filled cells Thereby certify that the information T. T. Borling	lass C Neat. Cement circulate 24 hours. Tested casing with alves above ground level off e N.M. ar. Above is true and complete to the best of my i gned by exton	4000# for 30 minutes- each casing string ins	-0 K.
Set and ceme 150 sacks cl W O C over 2 Installed value by State of Filled cells Thereby certify that the Information Thereby Certify that the Information	lass C Neat. Cement circulate 24 hours. Tested casing with alves above ground level off e N.M. ar. Above is true and complete to the best of my s	4000# for 30 minutes- each casing string ins	-0 K.
Set and ceme 150 sacks cl W O C over 2 Installed va by State of Filled cella	lass C Neat. Cement circulate the hours. Tested casing with alves above ground level off e N.M. ar.	4000# for 30 minutes- each casing string ins	-0 K.
Set and ceme 150 sacks cl W O C over 2 Installed va by State of Filled cella	lass C Neat. Cement circulate 24 hours. Tested casing with alves above ground level off e N.M. ar.	4000# for 30 minutes- each casing string ins	-0 K.
Set and ceme 150 sacks cl W O C over 2 Installed va by State of Filled cella	lass C Neat. Cement circulate 24 hours. Tested casing with alves above ground level off e N.M. ar.	4000# for 30 minutes- each casing string ins	-0 K.
Set and ceme 150 sacks cl W O C over 2 Installed va by State of	lass C Neat. Cement circulate 24 hours. Tested casing with alves above ground level off e N.M.	4000# for 30 minutes-	-0 K.
Set and ceme 150 sacks cl W O C over 2 Installed va by State of	lass C Neat. Cement circulate 24 hours. Tested casing with alves above ground level off e N.M.	4000# for 30 minutes-	-0 K.
Set and ceme 150 sacks cl W O C over 2 Installed va by State of	lass C Neat. Cement circulate 24 hours. Tested casing with alves above ground level off e N.M.	4000# for 30 minutes-	-0 K.
Set and ceme 150 sacks cl W O C over 2 Installed va by State of	lass C Neat. Cement circulate 24 hours. Tested casing with alves above ground level off e N.M.	4000# for 30 minutes-	-0 K.
Set and ceme 150 sacks cl W O C over 2 Installed va by State of	lass C Neat. Cement circulate 24 hours. Tested casing with alves above ground level off e N.M.	4000# for 30 minutes-	-0 K.
Set and ceme 150 sacks cl W O C over 2 Installed va by State of	lass C Neat. Cement circulate 24 hours. Tested casing with alves above ground level off e N.M.	4000# for 30 minutes-	-0 K.
Set and ceme 150 sacks cl W O C over 2 Installed va by State of	lass C Neat. Cement circulate 24 hours. Tested casing with alves above ground level off e N.M.	4000# for 30 minutes-	-0 K.
Set and ceme 150 sacks cl W O C over 2 Installed va by State of	lass C Neat. Cement circulate 24 hours. Tested casing with alves above ground level off e N.M.	4000# for 30 minutes-	-0 K.
Set and ceme 150 sacks cl W O C over 2 Installed va by State of	lass C Neat. Cement circulate 24 hours. Tested casing with alves above ground level off e N.M.	4000# for 30 minutes-	-0 K.
Set and ceme 150 sacks cl W O C over 2 Installed va by State of	lass C Neat. Cement circulate 24 hours. Tested casing with alves above ground level off e N.M.	4000# for 30 minutes-	-0 K.
Set and ceme 150 sacks cl W O C over 2 Installed va by State of	lass C Neat. Cement circulate 24 hours. Tested casing with alves above ground level off e N.M.	4000# for 30 minutes-	-0 K.
Set and ceme 150 sacks cl W O C over 2 Installed va	lass C Neat. Cement circulate 24 hours. Tested casing with alves above ground level off e	4000# for 30 minutes-	-0 K.
Set and ceme 150 sacks cl W O C over 2	lass C Neat. Cement circulate	4000# for 30 minutes-	-0 K.
Set and ceme 150 sacks cl	Lass C Neat. Cement circulate	ea.	
Set and ceme	ONNO . COMONOCA MITON	- 3	
	ented at 3950'. Comented with	950 sacks class C and	ව •
Ran 126 Jts	and 1 cut jt. 3932' of 4 1/2	·• - 박=→= • - O D K=55 ST & C Cacin	σ.
Reached T D	of 7 7/8 hole at 3950' at 4	n m li=li=77	
, Describe Proposed of Completed O work) SEE RULE 1703.	perations (Clearly state all pertinent details, a	and give pertinent dates, including	estimated date of starting any proposed
OTHER		OTHER	L
ILL OR ALTER CASING []		SING TEST AND CEMENT JOB A	
MPGRARILY ABANDON	r)	MMENCE DRILLING OPKS.	PLUG AND ABANDONMENT
ERFORM REMEDIAL WORK	PLUG AND ABANDON RES	MEDIAL WORK	ALTERING CASING
		Annes	
	NTENTION TO:		REPORT OF:
Check	Appropriate Box To Indicate Natur	re of Notice, Report or Otl	her Data
	3565 G L		Lea
	15, Elevation (Show whether DF,	RT, GR, etc.)	12. County
LINE, SECT	TOWNSHIP	RANCE DO LI NMPM.	
THE East LINE, SECT	22 TOWNSKIP 21-S	36-E	
UNIT LETTER	FEET FROM THE DOUBLE L	THE AND DOU FEET TROM	Eumont
	990 FEET FROM THE South	660	10. Field and Pool, or Wildow
• • • • • • • • • • • • • • • • • • • •	Lesution of Well		
Address of Operator Box 670, Hobbs, N.M. 88240			9. Well No.
Gulf Oil Corporation			Harry Leonard (NCT-A)
Name of Operator			6. Farm or Lease Name
OIL X GAS WILL	OTHER-		
	The second of the second secon		7. Unit Agreement Bane
SUNIUS Person albit dan ton oof Person dan dan	RY NOTICES AND REPORTS ON WE	LLD TO A DIFFERENT RESERVOIR, CROSSISSI	
Chill	OV HOTICES AND DEPOSES OF THE	116	B-1732
PERATOR			5, State Off & Gas Leave No.
			State XX Fee
AND OFFICE			5a. Indicate Type of Leaso
		TATION COMMISSION	Effective 1-1-65
H.E. J.5.G.S.		NEW MEXICO OIL CONSERVATION COMMISSION	
ANTAFE TLC J.5.G.S.	NEW MEXICO OIL CONSERV	ALTION COMMISSION	C-102 and C-103
J,5.G.S.	MEM WEXICO OIL CONSERV	ALTION CONNECTION	Form C-103 Supersedes Old

RELETANIAN.