

NO. OF COPIES RECEIVED	
DISTRIBUTION	
AMT. FE	
ILL	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-101
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDARY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO PULL OR TO CEMENT OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT TO PULL OR TO CEMENT FOR SUCH PROPOSALS.)		5a. Indicate Type of Lease State ☒ Fee ☐ 5. State Oil & Gas Lease No.
OIL WELL ☐ GAS WELL ☒ OTHER ☐ Name of Operator Amoco Production Company Address of Operator P. O. Drawer A, Levelland, Texas 79336 Location of Well UNIT LETTER <u>I</u> <u>3300</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>2</u> TOWNSHIP <u>21-S</u> RANGE <u>36-E</u> N.M.P.M.		7. Unit Agreement Name 8. Form or Lease Name State "C" Tract 11 9. Well No. 5 10. Field and Pool, or Wildcat Eumont Queen
11. Elevation (Show whether DF, RT, GR, etc.) 3509 GR		12. County Lea

5. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐		CASING TEST AND CEMENT JOB ☐	
OTHER <u>Additional Completion</u> ☒		OTHER ☐	

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to increase production by perforating additional pay. Set retrievable bridge plug at 3400' and perforate Yates Seven Rivers Zone interval 2679', 2695', 2743', 2778'-81', 2811', 2827', 2867', 2903'-07', 2923'-27', 2936', 3003'-09', 3195', 3231', 3266'-70', and 3291' with 2 JSPF. Acidize perfs with 3600 gals 15% DS-30 Western Acid. Frac perfs with 32,000 gals. Western Titan I containing 2 gals FS-F fluorosurfactant per 1000 gals, 8,000 gals CO₂, 40,000 pounds 20-40 mesh sand and 10,000 pounds 10-20 mesh sand. Swab back load and evaluate Yates-Seven Rivers interval prior to pulling bridge plug.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ray W. Cox TITLE Administrative Assistant DATE 9-12-77

REMOVED BY _____ TITLE _____ DATE _____

ORDINATIONS OF APPROVAL, IF ANY:
0; 3 - NMOC - H 6665, 1 - Div., 1 - Susp., 1 - RC