

N.M.O.C.D. COPY

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE

(See other in-
structions on
reverse side)Form approved,
Budget Bureau No. 42-R355.6.

5. LEASE DESIGNATION AND SERIAL NO.

NM-14791

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

SRN-1170

8. FARM OR LEASE NAME

New Mexico Federal Comm.

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLOCK AND SURVEY
OR AREA

Sec. 5, T-21-S, R-32-E

12. COUNTY OR
PARISH

13. STATE

Lea N. M.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other _____

b. TYPE OF COMPLETION:

NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ Other _____

2. NAME OF OPERATOR

Cleary Petroleum Corporation

3. ADDRESS OF OPERATOR

P. O. Drawer 2358, Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface 660' FEL & 3300' FSL

At top prod. interval reported below

At total depth

14. PERMIT NO.

DATE ISSUED

Letter of

5-11-77

15. DATE SPUDDED

5-21-77

16. DATE T.D. REACHED

7-12-77

17. DATE COMPL. (Ready to prod.)

7-27-77

18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*

3673' GR; 3691' KB

19. ELEV. CASINGHEAD

3670'

20. TOTAL DEPTH, MD & TVD

14,348'

21. PLUG, BACK T.D., MD & TVD

14,251'

22. IF MULTIPLE COMPL.,
HOW MANY*

23. INTERVALS
DRILLED BY

ROTARY TOOLS

CABLE TOOLS

0 - 14,348'

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

13,908 - 13,960' Morrow

25. WAS DIRECTIONAL
SURVEY MADE

No

26. TYPE ELECTRIC AND OTHER LOGS RUN

Compensated Acoustic Velocity, Forxo-Guard,
Radioactivity, Micro-Seismogram, Acoustic Velocity Neutron, 4-Arm Dip

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

* Circulated Cement

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
13 3/8"	54.5#	485'	17 1/2"	650 sx*	---
9 5/8"	40, 43.5&47#	5224'	12 1/4"	1st st-700 sx, DV tool set @ 3100', 2nd - 1625 sx*	---
5 1/2"	17 & 20#	14347'	7 7/8"	875 sx	---

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2 7/8"	13760'	13760'

31. PERFORATION RECORD (Interval, size and number)

13,908-14'	0.39" holes	7 holes
13,940-60'	0.39" holes	21 holes

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
None	

33.*

PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)					WELL STATUS (Producing or shut-in)	
9-8-77		Flowing					Producing	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO	
9-8-77	24	18/64"	—————→	45	3400	0	75556	
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)		
2100	0	—————→	45	3400	0	51.9		

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

Sold

TEST WITNESSED BY

Clarence Forister

35. LIST OF ATTACHMENTS

Logs, C-122, Deviation Report

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED Douglas W. Rice TITLE Assistant Dist. Prod. Mgr. DATE 9-13-77

*(See Instructions and Spaces for Additional Data on Reverse Side)

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROSITY ZONES: SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES				38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TRUE VERT. DEPTH
				Rustler Anhy.	1310'	
				Yates	3164'	
				Capitan Reef	3376'	
				Delaware Mtn.		
				Sands	5225'	
				Bone Springs	8464'	
				Wolfcamp	11030'	
				Strawn	12076'	
				Atoka Sand	12864'	
				Atoka Carbonates	13224'	
				Morrow Sands-		
				Upper	13772'	
				Morrow Sands-		
				Lower	14156'	
				Barnett Shale	14298'	