

NEW MEXICO OIL CONSERVATION COMMISSION

3-NMOCC-HOBBS
1-R. J. STARRAK-TULSA
1-A. B. CARY-MIDLAND
1-M. MERCHANT-ENGR.
1-FILE

1-MESA-MIDLAND
1-BELCO-MIDLAND
1-SOUTHLAND-MIDLAND
1-BH, FIELD CLERK

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
L-723

SUNDARY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR OPERATIONS TO BE LIFTED OR RETURNED TO A DIFFERENT RESERVOIR.
USE MAPS, LOCATION FOR PERMIT AND (DO NOT CHECK) FOR DATA PURPOSES.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. Unit Agreement Date -
2. Name of Operator Getty Oil Company	8. Farm or Lease Name Getty "35" State
3. Address of Operator P. O. Box 730, Hobbs, New Mexico 88240	9. Well No. 1
4. Location of Well UNIT LETTER <u>K</u> <u>2310</u> FEET FROM THE <u>South</u> LINE AND <u>1650</u> FEET FROM THE <u>West</u> LINE, SECTION <u>35</u> TOWNSHIP <u>21-S</u> RANGE <u>34-E</u> NMPL.	10. Field and Pool, or Wildcat Grama Ridge Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 3675.8 GR	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8-17-78 - Drilled 9 1/2" hole to 10,832'. Ran 266 jts. (10,832') of 7 5/8" (39,33.7, & 29.7#) casing & set at 10,832'. Halliburton cemented in three stages:

Stage 1: 175 sxs Lite Wate, 3# gilsonite, 1/4# flocele, .6 Halad 22, and 300 sxs. Class "H" cement with 3# salt, 3# gilsonite, 1/4# flocele, & .8 Halad 22.

Stage 2: 375 sxs Lite Wate cement, 5# gilsonite, 1/4# flocele, .6 Halad 22, & 200 sxs Class "H" cement with 3# salt, .8 Halad 22.

Stage 3: 150 sxs Thick-Set, 5# gilsonite, 1/4# flocele, 2% CaCl, 525 sxs Lite Wate, 3# Gilsonite, 1/4# flocele, and 200 sxs Class "C" cement.

Total cement - 1,955 sxs.

8-18-78 - Cement did not circulate. Jarrel ran Temperature Survey and found top of cement at 2900'.

WOC 24 hrs. Tested casing to 2000#. O.K.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R. Crockett TITLE Area Superintendent DATE 1-15-79
Date R. Crockett Orig. Signed by Jerry Sexton
APPROVED BY Dist 1. Supv. TITLE DATE JAN 12 1979
CONDITIONS OF APPROVAL, IF ANY: