

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SAN ANTONIO	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-101
Revised 1-1-65

5A. Indicate Type of Lease	
STATE <input checked="" type="checkbox"/>	FEE <input type="checkbox"/>
5. State Oil & Gas Lease No. E-1923	

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. Type of Work		7. Unit Agreement Name	
b. Type of Well DRILL <input checked="" type="checkbox"/> DEEPEN <input type="checkbox"/> PLUG BACK <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/> SINGLE ZONE <input checked="" type="checkbox"/> MULTIPLE ZONE <input type="checkbox"/>		8. Farm or Lease Name South Wilson State Com	
2. Name of Operator TEXAS OIL & GAS CORP		9. Well No. 1	
3. Address of Operator 900 Wilco Bldg., Midland, Texas 79701		10. Field and Pool, or Wildcat Undesignated (Morrow)	
4. Location of Well UNIT LETTER J LOCATED 1830 FEET FROM THE south LINE AND 1980 FEET FROM THE east LINE OF SEC. 14 TWP. 21S RGE. 34E NMPM		12. County Lea	
19. Proposed Depth 12,750'		19A. Formation Morrow	
20. Rotary or C.T. Rotary		21. Elevations (Show whether DF, RT, etc.) 3677.9 Gr	
21A. Kind & Status Plug. Bond Blanket- Renewed & upgraded to \$50,000		21B. Drilling Contractor Warton	
22. Approx. Date Work will start April 25, 1978			

23.

PROPOSED CASING AND CEMENT PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
17-1/2"	11-3/4"	42	500	700	SURF
11"	8-5/8"	32	5600	2400	SURF
7-7/8"	5"	15	12750	960	9000

- 1) Drill 17 1/2" hole to 500' with FW spud mud and set 11-3/4", 42#, H-40, ST&C casing. Circulate cement to surface.
- 2) Nipple up BOP stack (see attached diagram) and drill out with 11" bit using brine water. Drill through salt w/brine and mix gel & LCM for lost circulation in Basal Yates. Set 8-5/8", 32#, S-80 & K-55, ST&C @ 5600' or top of Delaware. Cement to surface using a DV tool at the top of the salt section (approx 1600') for 2nd stage job.
- 3) Drill out with 7-7/8" bit using FW. Drill to 10,600' (into the Wolfcamp) and pressure up on hole to test integrity to 11.7 PPG. If hole stands up, drill to TD, adjusting weight as necessary for gas control with gel and barite. Set 5" casing from TD back to surface and cement in place. If hole will not tolerate 11.7 PPG mud, set 7", 26#, N-80, FJ liner 5400'-10600' and drill to TD w/6" bit for completion through a 4 1/2" production liner set 10400-12750'.

Gas under Cities Services Co & ARCO is partially dedicated and under Phillips, Union of California, Wilson, Wyoming is not dedicated.

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE. GIVE BLOWOUT PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed S.P. Baker (S.P. Baker) Title District Drilling Engineer Date April 13, 1978

(This space for State Use)

APPROVED BY [Signature] TITLE SUPERVISOR DISTRICT

CONDITIONS OF APPROVAL: IF ANY, THE COMMISSION MUST BE NOTIFIED 24 HOURS PRIOR TO RUNNING CASING.

APPROVAL VALID FOR 90 DAYS UNLESS DRILLING COMMENCED,

EXPIRES

APR 17 1978