

State L-922 No. 2
1980' FEL, 1780' FSL
Sec. 28, T-21-S, R-34-E
Lea County, New Mexico

Page 2

- 10/18/85 - 12 Hrs SITP 2000#, flow 16 BLW on 16/64" chk in 3 1/2 hrs. FTP 2000# to 175# Westerr Co. acidized perf 12,169'-12,403' (OA) w/4000 gal 20% NEFE HCL acid + 100 RCN Balls AIR 4 1/2 BPMR w/6400# TP, Max TP 7500#, w/perfs balled off. ISDP 4600#, 5 min 4400#, 15 Min 4100#, SI 30 min Flowed 145 BLW in 4 Hrs on 48/64" chk to 12/64" chk, FTP 50# to 4000#, last hr flowed 3200 MCFPD w/spray of oil & wtr on 12/64" chk, FTP 4000#, short 27 BLW.
- 10/19/85 - 12 Hrs SITP 5800#. Flow well as follows: 3 1/2 Hrs 6/64" chk 1400 MCFPD, FTP 5800# - 5450#. 2 Hrs 12/64" chk 3200 MCFPD, FTP 5450# - 4000#, made small spray of oil & load wtr while flowing, RD Rel rig.
- 10/23/85 - Ran 4 point potential test as follows: SITP 5050# DWT, ran 12 hr BHP bombs to 12,140'.
- | | |
|------|--|
| 1 Hr | 570 MCFPD + 3 B. Cond + 0 BW, FTP 3773# 7/64" chk, 510# BP |
| 1 Hr | 750 MCFPD + 3.5 B. Cond + 0 BW, FTP 2658# 8.5/64" chk, 510# BP |
| 1 Hr | 680 MCFPD + 4 B. Cond + 14 BW, FTP 1720# 10/64" chk, 510# BP |
| 1 Hr | 1150 MCFPD + 6.5 B. Cond + 30.5 BW, FTP 1894#, 17/64" chk, 510# BP |
- POH bombs, RIH 48 Hr BHP bombs, flow 1 hr @ 2300 MCFPD + 23 B. Cond + 4 BW FTP 1660# on 17/64" chk w/510# BP. SI for BHP buildup.
- 10/25/85 - 40 Hrs SITP 5225# DWT, Bennett & Cathey WL POH BHP bombs CAOF 1261 MCFPD, SI well.