

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. <u>B-1537</u>
7. Unit Agreement Name
8. Farm or Lease Name <u>STATE 'D'</u>
9. Well No. <u>14</u>
10. Field and Pool, or Wildcat <u>ELMONT GAS</u>
12. County <u>LGA</u>

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator <u>CONTINENTAL OIL COMPANY</u>
3. Address of Operator <u>P.O. Box 460 Hobbs, N.M. 88240</u>
4. Location of Well UNIT LETTER <u>A</u> , <u>915</u> FEET FROM THE <u>NORTH</u> LINE AND <u>990</u> FEET FROM THE <u>EAST</u> LINE, SECTION <u>15</u> TOWNSHIP <u>21 S</u> RANGE <u>36 E</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOBS <input type="checkbox"/> OTHER <u>SET 8 5/8" SURFACE CASING</u> <input checked="" type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled a 12 1/4" hole to 1328' K.B. Set 8 5/8" 24" casing AT 1328' KB as follows:

- Pump 5 bbl water spacer and follow w/ 700 sx Class "C" cmt w/ additives.
- displace w/ 82 bbls fresh water. Bump plug to 1200 psi. (held o.
- Circulate 150 sx to surface. W.O.C. 18 hrs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Wm. A. Butterfield TITLE Administrative Supervisor DATE 8-2-78
 Original Signed by Jerry Beaton
 APPROVED BY Don L. Smith TITLE _____ DATE AUG 8 1978
 CONDITIONS OF APPROVAL, IF ANY OCC. [6] FILE

RECEIVED

AUG 21 1978

CP CONSERVATION COMM.
DOES, R. M.