

5. APOLLO WL PERF GLORIETA SET I 5274-80, 5294-96, 5319-26 & 5340-42, 1 JSPF, TOTAL 21 HOLES USING 4" OD, 22.7 GM, .43" EH CSG GUN (GOEX DML-23 CHARGES), 120° PHASED, NON-CENTRALIZED VIA SCHLUMBERGER GR/CN-FDL DATED 10-4-78.
6. RIH W/5-1/2", 15.5# BAKER MOD R-3 DG PKR (SUN OWNED STOCK) & API SN ON 2-3/8", 4.7#, J-55 YB WORKSTRING TO ±5150'. SET PKR.
7. ~~MIRU WESTERN CO.~~ **BJ-TITAN** TRAP 1000 PSI CP. ACIDIZE GLORIETA PERFS 5274-5342 W/5000 GALS 20% NEFEHCL W/ADDITIVES* IN ONE STAGE. AIR 6 BPM. MAX TREATING PRESS 5000 PSI. EST WHTP 3000 PSI. DIVERT ACID USING 30 7/8", 1.1 SP GR, RCNBS. DROP BALLS IN CLUSTERS OF 5 SPACED EVENLY THRU OUT ACID. FLUSH TO BTM PERF W/25 BBLS NE 2% KCL FSH WTR.
8. SWAB BACK L&AW (±170 BBLS). EVALUATE FE RATE AND CONTENT. RLSE PKR, LWR THRU PERFS, REV OUT BS & POH W/2-3/8" WS LAYING DOWN.
9. RIH W/31' BP MUD ANCHOR, PERF SUB, SN, 4 JTS 2-3/8" TBG & 5-1/2" X 2-3/8" TAC ON 2-3/8", 4.7#, J-55 PROD TBG. TS ±5402', MA ±5370', PS ±5366', SN ±5365', TAC ±5241'. ND BOP. NU WH.
10. RIH W/2" X 1.5" X 16' RHBC ROD PUMP ON 76 TAPER 'K' GRADE ROD STRING (146 - 3/4" RODS, 68 - 7/8" RODS). SPACE OUT AS NECESSARY. CHECK PUMP ACTION & RLSE RIG.