

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

3-NMOCC-HOBBS
1-R. J. STARRAK-TULSA
1-A. B. CARY-MIDLAND
1-MYM, ENGR.
1-CM, FOREMAN
1-BH, FIELD CLK
1-FILE
1-CP, CLK
1-SABINE, MIDLAND
1-PHILLIPS, ODESSA

5a. Indicate Type of Lease State ☒ Fee ☐
5. State Oil & Gas Lease No. LG-6004
7. Unit Agreement Name -
8. Form or Lease Name Getty 36 State Com.
9. Well No. 1
10. Field and Pool, or Wildcat Grama Ridge
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO RE-OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT TO DRILL OR RE-OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR")

1. ☒ OIL WELL ☒ GAS WELL ☐ OTHER-
2. Name of Operator Getty Oil Company
3. Address of Operator P. O. Box 730, Hobbs, New Mexico 88240
4. Location of Well UNIT LETTER F 1980 FEET FROM THE North LINE AND 1650 FEET FROM THE West LINE, SECTION 36 TOWNSHIP 21S RANGE 34E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

3674' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	COMMENCE DRILLING OPS. ☐
PULL OR ALTER CASING ☐	CASING TEST AND CEMENT JOBS ☒
OTHER ☐	ALTERING CASING ☐
	PLUG AND ABANDONMENT ☐
	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3-7-79 Drilled 12 1/4" hole to 5503'. Ran 133 jts. 9 5/8" 36# S-80 & K-55 casing and set at 5502'. FC at 5459'. DV at 4156'. Baskets at 4204' and 4247'. Broke circulation.

Dowell cemented in two stages:

First Stage: 250 sxs Class "C" Lite Wate cement, 5# salt, 5# Kolite, 1/4# flocl, 100 RFC 7 1/2% Kolite, 1% CaCl, and 200 sxs Class "C" cement with 1/4# flocl. Opened DV tool. Circulated 125 sxs cement. Ran Drilprodco Volume Meter.

Second Stage: 2,190 sxs Class "C" Lite Wate cement, 5# salt, 5# Kolite, 1/4# flocl. Tailed in with 300 sxs Class "C" cement with 1/4# flocl. Circulated 250 sxs cement. DV tool did not close. Went 30 bbls. passed displacement.

Total cement: 2,940 sxs.

WOC

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Dale R. Crockett</u>	TITLE <u>Area Superintendent</u>	DATE <u>3-9-79</u>
Orly Signed By <u>Jerry Sexton</u>		
Disc 1, Supv.		
APPROVED BY _____	TITLE _____	DATE <u>12 1979</u>
CONDITIONS OF APPROVAL, IF ANY:		