

Form 9-331
Dec. 1973Form Approved.
Budget Bureau No. 42-R1424UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well2. NAME OF OPERATOR
CONOCO INC.3. ADDRESS OF OPERATOR
P. O. Box 460, Hobbs, N.M. 882404. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 990' ENL & 1180' FWL
AT TOP PROD. INTERVAL: same
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF

☐
☐
☐
☐
☐
☐
☒
☐RECEIVED
JUL 7 1980
U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

5. LEASE

LC 031741 a

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

NMFU

8. FARM OR LEASE NAME

Hawk A

9. WELL NO.

7

10. FIELD OR WILDCAT NAME

B Linebry

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 8, T-21S, R-37E

12. COUNTY OR PARISH

Lea

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRU 6-30-80. Set CIBP @ 6200' & Spotted 3 SK. cmt. on top of CIBP. Spotted 168 gal. 15% HCl @ 6039'-5867'. Lost perf. gun in hole, but fished it out. Perf gun cracked CIBP. Set another CIBP @ 6197' & spotted 3 SK. (17') on top of CIBP. Perf. lower Blinebry @ 5904', 5907', 5912', 5915', 5921', 5924', 5941', 5988', 5991', 5997', 6000', 6018', 6035', 6039'. Acidized w/ 28 bbls. 15% HCl-NE. Frac'd w/ 14,196 gal. gel. & 9408 gal. 15% HCl-NE. Perf. upper Blinebry @ 5695', 5719', 5735', 5739', 5744', 5763', 5768', 5778' w/ 1 JSPF. Acidized w/ 672 gal. 15% HCl-NE-FE. Frac'd w/ 302 bbls. gel & 214 bbls. 15% HCl-NEFE. Set 2 3/8" Ag. @ 6067'

Well prodp. 52 BOPD, 18 BWPD, 86 McFPD on 7-31-80
Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED John A. Butterfield TITLE Administrative Supervisor

DATE 8/4/80

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:USGS-5
NMFU-4

TITLE _____

DATE _____

AUG 11 1980

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO