Form 9-331 Dec. 1973

Form Approved.

UNITED STATES					
DEPARTMENT OF THE INTERIOR					
CECLOGICAL SURVEY					

Budget	Bureau	No.	42-R142

OMILE STATES	5. LEASE		
DEPARTMENT OF THE INTERIOR	LC-031741 # (g)		
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME		
	N.M.F.U.		
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME		
1. oil gas other	Hawk A		
	9. WELL NO.		
2. NAME OF OPERATOR	· ·		
Conoco Inc.	10. FIELD OR WILDCAT NAME		
3. ADDRESS OF OPERATOR	Drinkard/Blinebry		
P. D. Box, Hobbs, N.M. 88240	11. SEC., T., R., M., OR BLK. AND SURVEY OR		
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA		
halow)	Sec. 8, T-215, R-37E		
AT SURFACE: 990 FNL & 1980 FWL			
AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE		
AT TOTAL DEPTH:	Lea N.M.		
Al Torre Del III.	14. API NO.		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,			
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)		
	3540.1 GR		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF			
FRACTURE TREAT			
SHOOT OR ACIDIZE			
REPAIR WELL	(NOTE) Report results of mile completion or zone		
PULL OR ALTER CASING	Uchange phi Forth 9-330.)		
MULTIPLE COMPLETE	SEI SURVEY		
CHANGE ZONES	OGICH MEXICO		
ABANDON*	U. S. GEOL NEW ME		
(other) Set production esq. X	U. S. GEOLOGICAL SURVEY HOBBS, NEW MEXICO		
	· · · · · · · · · · · · · · · · · · ·		
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state	e all pertinent details, and give pertinent dates.		
including estimated date of starting any proposed work. If well is di	rectionally drilled give subsurface locations and		
measured and true vertical depths for all markers and zones pertinen	t to this work.)*		
NILLA COUNT TO A 10 TA -			
Drilled 6880' T.D. 9-10-79, A	on esq. as follows:		
	· · · · · · · · · · · · · · · · · · ·		
quide shoe, shoe jt, FC, 70 jts. 5/2"	esq. DV tool & 100 more its		
	▼		
5 1/2", 15.5# & 17" csq. Bottom of csq	0 1959' NV + 1 0 41000		
2 12 , 13.3 A 11 239.	. 6 6838 , DV 1801 W 7002.		
D) 		
Pmpd. (e40 sx. Class "C" cmt. W/ additi	ves. Second stage; pmpd.		
() () () () () () () () () ()			
1120 sx. Howco Lite-wate of 18%	sull. Circ. 73 SK. ent.		
	· · · · · · · · · · · · · · · · · · ·		
to surface. Rig down & release rig 9-13-	74.		
	•		
Subsurface Safety Valve: Manu. and Type	Set @ Ft.		
19. I hamby partify that the foregoing is true and source.			
18. I hereby certify that the foregoing is true and correct	•		
SIGNED Web A - The Wifeld TITLE Admin. Supe	CVISO DATE 9/BURAN		
	TO FIN KEUDING		
(This space for Federal or State offi	ed avoctoff tou		
	1070 1000		
APPROVED BY TITLE TOTALL TO SET	SEP 17 1979		
	U. S. GEOLOGICAL SURVEY		
US65-5	- AI - III - T		
NMFU-4	U. S. GEOLOGICAL MEXICO		
FILE	I HORBS: I'M		

沙红地

*See Instructions on Reverse Side