

NEW MEXICO OIL CONSERVATION COMMISSION

3-NMOCC-HOBBS 1-H-FILE
1-R.J. STARRAK-TULSA 1-FILE
1-A.B. CARY-MIDLAND 1-BB-OFC TECH
1-PJB, ENGR. 1-SOUTHLAND, MIDLAND
1-BELCO-MIDLAND 1-MESA-MIDLAND

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State C.R. & Gas Lease No.
LG-1487

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR NOTICES TO ABANDON OR TO CEASE PRODUCTION OF A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT TO ABANDON WELL OR TO CEASE PRODUCTION OF A DIFFERENT RESERVOIR.

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER-

7. Unit Agreement Name

2. Name of Operator
GETTY OIL COMPANY

6. Name of Lease Name

GETTY "35" STATE COM.

3. Address of Operator
P. O. BOX 730, HOBBS, NEW MEXICO 88240

9. Well No.

2

4. Location of Well

UNIT LETTER H 1980 FEET FROM THE NORTH LINE AND 660 FEET FROM
EAST 35 21-S 34-E
THE LINE, SECTION TOWNSHIP RANGE NMPL.

10. Field and Pool, or Wildcat

GRAMMA RIDGE E. MORROW

15. Elevation (Show whether DF, RT, GR, etc.)

3658 G.L.

12. County

LEA

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPER. ☒
CASING TEST AND CEMENT JOBS ☐
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103.

3-8-80 Drilled 12-1/4" hole to 5550'. Ran 52 Jts. (2199') of 9-5/8" 8Rd N-80 40# LT&C R-3 and 79 Jts. (3314') of 9-5/8" 8rd J-55 36# LT&C R-3. Guide Shoe - 5547'; Float Collar - 5502'; DV - 3842'; Cement Basket - 3886' - 3928'. and cemented as follows:

FIRST STAGE: 250 sxs. Howco Lite w/6# Salt, 3# Gilsonite & 1/4# Flocele/sk. Tailed in w/ 250 sxs. Class "C" w/1/4# Flocele. Bumped plug @ 6:30 A.M. 3-8-80 w/422 Bbls. Wtr. & 400# Pressure. Did not Circulate. Dropped bomb and opened DV Tool @ 3845'. Pumped approx. 200 Bbl. per hr. No circulation for 3-1/2 hrs.

SECOND STAGE: 2000 Sxs. Howco Lite w/15# Salt, 5# Gilsonite, 1/4# Flocele/sk. Tailed in w/200 Sxs. Class "C" w/1/4# Flocele/sk. Bumped plug @ 12:00 P.M. 3-8-80 w/800# pressure and 260 Bbls. Wtr. Circulated last 60 Bbls. No Cement. Shut Down.

Worth Well ran Temperature Survey and found top of good Cement @ 1720'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Dale R. Crockett

TITLE AREA SUPERINTENDENT

DATE 3-10-80

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY: