

NO. OF COPIES RECEIVED	
DISTRIBUTION	
DATE	
FILE	
S.G.S.	
AND OFFICE	
PERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

3 - OCD-Hobbs 1 - File
 1 - R.J. Starrak-Tulsa
 1 - A.B. Cary-Midland
 1 - PJB - Engr.

Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

5a. Indicate Type of Lease	State ☒ Fee ☐
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name	Getty 6 State Com.
9. Well No.	1
10. Field and Pool, or Wildcat	Wildcat
12. County	Lea

SUNDARY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR NOTICES TO ABANDON OR TO OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
 USE APPLICATION FOR PERMIT TO PRODUCE OIL, FOR OIL AND GAS OPERATIONS.)

OIL WELL ☐ GAS WELL ☒ OTHER ☐

Name of Operator
 Getty Oil Company

Address of Operator
 P.O. Box 730, Hobbs, N.M. 88240

Location of Well
 UNIT LETTER Lot #11, 3500 FEET FROM THE North LINE AND 2200 FEET FROM
 THE West LINE, SECTION 6 TOWNSHIP 21-S RANGE 34-E N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)
 3753' GL

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
 NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6/21/80 - TD 12 1/4" Hole 5700' @ 12:30 AM Ran 141 jts. 9 5/8" 36# k-55 and 40# N-80 Csg. w/Halliburton Guide Shoe @ 5698-5700'; Float collar 5657-5659 and DV 3814-3817. Western cemented 9 5/8" as follows:

First Stage: 500 sxs. Pacesetter Lite, 15# salt, 1/4# Flocele, 5# Gilsonite, .2% AF-11 and 250 sxs. Class "C" Cement w/1/4# Flocele/sk.

6/22/80 -
Second Stage: 3300 sxs. Lite, 15# salt, 1/4# Flocele, 5# Gilsonite, .2% AF-11 and 250 sxs. Class "C" Cement, 1/4# Flocele. Circulated 35 sxs. Cement.

Total cement - 4300 sxs.

W.O.C. 18 hrs. Tested to 1200# for 30 min. ok.

16. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Dale R. Crockett</u>	TITLE <u>Area Superintendent</u>	DATE <u>6/23/80</u>
APPROVED BY <u>[Signature]</u>	TITLE <u></u>	DATE <u></u>
CONDITIONS OF APPROVAL, IF ANY		