

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.

1. oil ☒ gas ☐
well ☒ well ☐ other ☐
2. NAME OF OPERATOR
Post Petroleum
3. ADDRESS OF OPERATOR 1007 Ghls Tower West
Midland, Tx. 79701
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below)
AT SURFACE:
AT TOP PROD. INTERVAL: 1970/40
AT TOTAL DEPTH: 7580'
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐ ☐

FRACTURE TREAT ☐ ☐

SHOOT OR ACIDIZE ☐ ☐

REPAIR WELL ☐ ☐

PULL OR ALTER CASING ☐ ☐

MULTIPLE COMPLETE ☐ ☐

CHANGE ZONES ☐ ☐

ABANDON* ☐ ☐

(other) Casing Ran & Cemented ☐ ☐

5. LEASE
Llano NM 17252
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Llano 31 Federal
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Undesignated D-K ABO
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 21 T-20-S R-39-E
12. COUNTY OR PARISH 13. STATE
Lea New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3562.8 KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Cement 8 5/8" surface @ 1670' with 560 sacks Pacesetter Lite and 0.25 lbs. Cello-Seal/sack followed by 200 sacks Class "C" and 2% CaCl₂. Circulated 75 sacks to surface.

Cement 4 1/2" @ 7580' with 100 sacks containing Trinity Lite followed by 1000 sacks Class "C" with 10% salt, 0.6% CFR-2, and .3% AF11 in the first stage. Cemented the second stage with 100 sacks of Trinity Lite followed by 700 sacks Class "C", 10% salt, 0.6% CFR-2, 0.3% AF11. Circulated 125 sacks to surface.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Chris Mersphen TITLE Representative DATE 10-27-80

APPROVED BY
CONDITIONS OF

ACCEPTED FOR RECORD

(space for Federal or State office use)

P. Chastin

TITLE

DATE

OCT 31 1980

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side