

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION
 3-NMOCC-Hobbs
 1-W.A. Frnka-Tulsa
 1-L.R. Hall-Midland
 1-File
 1-Engr. PJB

Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

5a. Indicate Type of Lease	State ☒ Fee ☐
5. State Oil & Gas Lease No.	LG-6143

SUNDY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR APPLICATION TO OIL OR TO OIL OR GAS BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO OIL OR TO OIL OR GAS BACK TO A DIFFERENT RESERVOIR.")	
1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER	7. Unit Agreement Name
2. Name of Operator Getty Oil Company	8. Farm or Lease Name Getty 25 State
3. Address of Operator P.O. Box 730, Hobbs, N.M. 88240	9. Well No. 1
4. Location of Well UNIT LETTER <u>N</u> <u>1980</u> FEET FROM THE <u>West</u> LINE AND <u>660</u> FEET FROM THE <u>South</u> LINE, SECTION <u>25</u> TOWNSHIP <u>21-S</u> RANGE <u>34-E</u> N.M.P.M.	10. Field and Pool, or Wildcat Grama Ridge Morrow
11. Elevation (Show whether DF, RT, GR, etc.) 3671' G.L.	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	COMMENCE DRILLING OPNS. ☐
PULL OR ALTER CASING ☐	CASING TEST AND CEMENT JOBS ☒
OTHER ☐	OTHER ☐
PLUG AND ABANDON ☐	ALTERING CASING ☐
CHANGE PLANS ☐	PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9/12/80 Drilled 12 1/4" hole to 5600'.

9/13/80 Ran and set 132 jts. (5556') - 9 5/8" 40# S-80 and 36# K-55 8rd ST&C Casing and set at 5580'. Halliburton cemented as follows:
 1st Stage: 250 sxs. Halliburton Lite w/6# salt, 3# Gilsonite, 1/4# Flocele/sx. and tailed in w/250 sxs. Class "C" cement w/1/4# Flocele/sx. Plug down at 3:30 PM 9/13/80. Dropped bomb. Opened DV Tool at 3883'. Cement did not circulate.
 2nd Stage: 3000 sxs. Howco Lite w/15# salt, 5# Gilsonite, 1/4# Flocele/sx. and tailed in w/200 sxs. Class "C" cement w/1/4# Flocele/sx. Plug down at 9:00 PM, 9/13/80. Cement did not circulate.

9/14/80 WOC 18 hrs. Tested casing to 1500# - OK. Ran temperature survey and found top of cement at 2615'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Dale R. Crockett TITLE Area Superintendent DATE 9/22/80

APPROVED BY _____ TITLE _____ DATE _____
 CONDITIONS OF APPROVAL, IF ANY: