

COPIES RECEIVED		
DISTRIBUTION		
DATE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
2. Name of Operator <b>Kern Co.</b>	5. State Oil & Gas Lease No. <b>N.A.</b>
3. Address of Operator <b>250 Mid America Building, Midland, Texas 79701</b>	7. Unit Agreement Name <b>None</b>
4. Location of Well UNIT LETTER <b>G</b> <b>1980</b> FEET FROM THE <b>North</b> LINE AND <b>1980</b> FEET FROM THE <b>East</b> LINE, SECTION <b>7</b> TOWNSHIP <b>21S</b> RANGE <b>37E</b> N.M.P.M.	8. Farm or Lease Name <b>M. L. Goins</b>
	9. Well No. <b>#3</b>
	10. Field and Pool, or Wildcat <b>Eumont</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>3495 G.L.</b>	12. County <b>Lea</b>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10/3/80 Spudded 12 1/4" hole @ 1:30 A.M. & drilled to 320'.

10/4/80 Drilled to 345' in Redbeds. Ran 8 joints 23# 8 5/8" casing and cemented @ 345' with 300 sacks of cement. Cement circulated 75 sacks to surface. Tested casing and BOP to 800# and drilled cement plug at 2:45 A.M. Now drilling at 600 feet.

10/5/80 Drilling 7 7/8" hole in anhydrite and salt at 1700'.

10/6/80 Drilling 7 7/8" hole in anhydrite at 2630'.

10/7/80 Drilling 7 7/8" hole in lime and dolomite at 3020'.

10/8/80 Drilling 7 7/8" hole in lime and dolomite at 3385'.

10/9/80 Drilling 7 7/8" hole in lime and dolomite at 3585'.

10/10/80 Drilling 7 7/8" hole in sand and dolomite at 3785'.

10/11/80 Drilled 7 7/8" hole in sand and dolomite to 3900' and ran Density Neutron Fororo logs from 3899' to surface.

10/12/80 Ran 96 joints of 10.5# 4 1/2" J-55 casing and cemented @ 3899' with 1150 sacks Halliburton cement. Cement Circulated 200 sacks to surface.

10/13/80 Sunday could not move

10/14/80 Move out rotary tools.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED William P. Kern TITLE Engineer DATE 10/14/80

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: