INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and ratio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

٠

Northwestern New Mexico

| | | T. Canyon | T Oio Alamo | T. Penn. "B" |
|---------|-----------------|---|----------------------|-----------------|
| Т. | Anhy | T. Canyon T. Strawn12632 | T Kirtland-Fruitland | T. Penn. "C" |
| т. | Salt | T. Strawn <u>12052</u> T. Atoka <u>12850</u> | T Fictured Cliffs | T. Penn. "D" |
| В. | Salt | T. Miss | T Cliff House | _ T. Leadville |
| Т. | Yates3688 | T. Miss T. Devonian | T. Monufee | T. Madison |
| т. | 7 Rivers | T. Devonian | T. Deint Lookout | T. Elbert |
| Т. | Queen | T. Silurian | T. Manage | T McCracken |
| T. | Grayburg | T. Montoya | T. Mancos | T Ignacio Otzte |
| Т. | San Andres | T. Simpson | T. Gallup | T Granite |
| т. | Glorieta | T. McKee | Base Greenhorn | T. Granne |
| т. | Paddock | T. Ellenburger | T. Dakota | - I |
| | | | | |
| т. | Tubb | T. Granite | T. Todilto | |
| T. | Drinkard | T. Delaware XXX 5848 | T. Entrada | T |
| _ | • | T Bone Springs 8621 | T. Wingate | T |
| | 33053 | - Canitan Reet (Yhb | T. Chinie | T |
| л. т | | $\sim MOLIOW$ 10405 | T. Permian | T |
| | Cisco (Bough C) | T. MOLLOW CLAS. 15544 | . T. Penn. "A" | T |
| | | Barnett Shale 14150 GAS | SANDS OR ZONES | |
| No. | 1, from | to | No. 4, from | |
| No. | 2, from | | No. 5, from | to |
| No. | 3, from | | No. 6, from | to |

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

| No. 1, fromto | 0feet. | |
|---------------|--------|--|
| No. 2, fromto | | |
| No. 3, fromto | | |
| No. 4, fromto | 0fcet. | |

FORMATION RECORD (Attach additional sheets if necessary)

| From | To | Thickness in Feet | Formation | From | Тο | Thickness in Feet | Formation |
|------|----|----------------------|-----------|--------|--------|----------------------|--|
| | | | | 13,696 | 13,756 | 60' | Core #1-Rec. 60' 20# sand 80% shale |
| | | | | 13,856 | 13,816 | 60' | Core #2-Rec. 45' 9' sand 12' VF sand & siltstone & 24' of black shale. |
| | | | | | | | |