

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

3-NMOCD-Hobbs
1-PJB-Engr.
1-File
7-WIO's

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State ☒	Fee ☐
5. State Oil & Gas Lease No.	
L-5146	
7. Unit Approval No.	
8. Part of Lease Name	
Berry 5 State	
9. Well No.	
1	
10. Field and Pool, or Wildcat	
Undesignated	
12. County	
Lea	

SUNDY NOTICES AND REPORTS ON WELLS
DO NOT USE THIS FORM FOR NOTICES TO WELL OWNERS OR OTHERS. IT IS A DIFFERENT PAPER.
SEE INSTRUCTIONS FOR REVENUE AND OTHER INFORMATION ON THE REVERSE.

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER-

2. Name of Operator
GETTY OIL COMPANY

3. Address of Operator
P.O. Box 730, Hobbs, NM 88240

4. Location of Well
UNIT LETTER T 1980 FEET FROM THE South LINE AND 660 FEET FROM
THE West LINE, SECTION 5 TOWNSHIP 21S RANGE 34E NMPL.

11. Elevation (Show whether DF, RT, CR, etc.)
3731 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☒	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1593.

4/10/81 TD @ 10:45 a.m. Ran CNL-FDC, Dual Laterolog/MSFL from 11,698-5646'.

4/11/81 Sonic log from 11,698 to 5646'.

4/12/81 Ran 64 jts. (2403') 7" 8rd 26# NKT 95-S and 232 jts. 7" 26# N-80 LT&C. Shoe @ 11,720', F.C. @ 11,679', DV @ 8010'. 1st stage: Howco cemented with 350 sxs. Lite with .6% Halad 22, 3# gilsonite, 1/4# flocele, 3# salt. Tailed in with 300 sxs. class II, .6% Halad 22. Opened DV tool, circulated 4 hrs., 50 sxs. cement. 2nd stage: 900 sxs. Lite with .6% Halad 22, 3# gilsonite, 1/4# flocele, tailed in with 200 sxs. Class II with .6% Halad 22, 3# salt. Plug down @ 3:45 a.m. Did not circulate.

4/13/81 WOC 18 hrs. Pressured up on casing to 1200# for 30 min., OK. Ran temperature survey, found top of cement @ 1205'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED File R. Crockett TITLE Area Superintendent DATE 4/15/81

APPROVED BY John Smith TITLE Area Superintendent DATE 4/15/81

CONDITIONS OF APPROVAL, IF ANY: