

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

3-NMOCD-Hobbs
1-PJB-Engr.
1-File
7-WIO's
1-EP

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State ☒ Fee ☐
5. State Oil & Gas Lease No. L-5146
7. Unit Agreement Name
8. Farm or Lease Name Berry 5 State
9. Well No. 1
10. Field and Pool, or Wildcat Undesignated
12. County Lea

SUNDY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REOPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT TO DRILL (FORM C-101) FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER-

2. Name of Operator
Getty Oil Company

3. Address of Operator
P.O. Box 730, Hobbs, NM 88240

4. Location of Well
UNIT LETTER T 1980 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 5 TOWNSHIP 21S RANGE 34E NMPM.

13. Elevation (Show whether DF, RT, CR, etc.)
3731 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
☐ PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ FULL OR ALTER CASING ☐ OTHER	☐ REMEDIAL WORK ☐ COMMENCE DRILLING OPNS. ☒ CASING TEST AND CEMENT JOB ☐ OTHER
☐ PLUG AND ABANDON ☐ CHANGE PLANS ☐ OTHER	☐ ALTERING CASING ☐ PLUG AND ABANDONMENT ☐ OTHER

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3/21/81 Drilled 12 1/4" hole to 5642'. Ran 48 jts. (2075') 9 5/8" ST&C 8rd 40# S-80 R3 and 86 jts. (3538') 9 5/8" ST&C 8rd 36# and set @ 5642'. Float collar @ 5595', DV @ 3644-3677'. Western cemented:
1st stage: 300 sxs. Pace Setter Light Class "C" cement with 15# salt, 5# gilsonite, 1/4# Cello Seal, and 2% AFHD. Tailed in with 200 sxs. Class "C" cement with 1/4# Cello Seal. Bumped plug @ 4:10 a.m., 3/22/81, with 430 bbls. Dropped bomb Opened DV tool. Circulated @ 4:40 a.m.
2nd stage: 1100 sxs. PSL with 15# salt, 5# gilsonite, 1/4# Cello Seal, and 2% AFHD. Tailed in with 100 sxs. Class "C" cement with 1/4# Cello Seal. Bumped plug @ 9:55 a.m.

3/24/81 WOC 18 hrs. Presssured up on casing to 1200# for 30 minutes, OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Dale R. Crockett</u>	TITLE <u>Area Superintendent</u>	DATE <u>3/27/81</u>
APPROVED BY <u>[Signature]</u>	TITLE <u></u>	DATE <u>3/28/81</u>

CONDITIONS OF APPROVAL, IF ANY: