

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION  
 3-NMOCD-Hobbs  
 1-PBJ-Engr.  
 1-File  
 7-WIO's

Form C-103  
 Supersedes Old  
 C-102 and C-103  
 Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS  
 (DO NOT USE THIS FORM FOR PRODUCTION TO BE LIFTED UP TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT TO (FORM C-101) FOR SUCH PURPOSES.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. Name of Operator  
 GETTY OIL COMPANY

3. Address of Operator  
 P.O. Box 730, Hobbs, NM 88240

4. Location of Well  
 UNIT LETTER T 1980 FEET FROM THE South LINE AND 660 FEET FROM  
 THE West LINE, SECTION 5 TOWNSHIP 21S RANGE 34E NMPM.

5a. Indicate Type of Lease  
 State ☒ Fee ☐

5. State Oil & Gas Lease No.

7. Unit Agreement Name

6. Farm or Lease Name  
 Berry 5 State

9. Well No.  
 1

10. Field and Pool, or Wildcat  
 Undesignated

12. County  
 Lea

15. Elevation (Show whether DF, RT, GR, etc.)  
 3731 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	
OTHER <input type="checkbox"/>	
PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>
	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3/7/81 Ran 23 jts. (975') of 13 3/8" OD 48# H-40 R-3 casing with Howco float equipment. Howco Guide Shoe @ 1000', Howco float collar @ 956'. Western cemented with 635 sxs. Class "C" cement with 2% CaCl, 4% gel and 1/4# Flocele per sack. Tailed in with 200 sxs. of Class "C" cement with 2% CaCl. Total cement 835 sxs. Circulated 150 sxs.

3/8/81 WOC 18 hrs. Pressured to 1200# for 30 minutes. OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Dale R. Crockett TITLE Area Superintendent DATE 3/11/81

APPROVED BY Les Clements TITLE Oil & Gas Insp. DATE 3/11/81

CONDITIONS OF APPROVAL, IF ANY: