District I 1625 N. French Dr., Hobbs, NM 88240 District II				State of New Mexico Energy, Minerals & Natural Resource					Form C-101 Revised March 17, 1999 Submit to appropriate District Office			
811 S. 1st Street, Artesia, NM 88210 District III				Oil Conservation Divsiion					State Lease - 6 Copies			
1000 Rio Brazos I District IV	Rd., Aztec, N	M 87410		-	2040 Sou	th Pacheco			Fee Lease - 5 Copies			
2040 South Pache	co, Santa Fe,	NM 87505		S	Santa Fe,	NM 87505	5		t			
									AME	NDED REPORT		
APPLIC	CATION	FOR P	ERMIT 7	FO DRIL	L. RE-E	NTER. DE	EPEN.	PLUGBAC	K. OR ADD) A ZONE		
			erator Name ar	· · · · ·			,	1	² OGRID Numbe			
BP AMERICA	PRODUCTIO	ON COMPAN	1 X					000778				
501 WESTLAK		LVD, RM 5	5.174; HOU	STON, TX 7	77079			30-02.5	30-025-27254			
$\frac{^{4}\text{Prope}}{7}$	rty Code				⁵ Property				⁶ Well No.			
$ \propto r$		<u>l</u>	<u> </u>		MAE F. C ⁷ Surface			l		1		
				T	T			1	T1			
UL or lot no.	Section	Township	Range	Lot. Idn	Feet from		outh Line	Feet from the	East/West line	County		
B	7	215	<u> </u>	<u> </u>	660		ORTH	1980	EAST	IEA		
	-	r	Proposed	Bottom Ho	ole Locati	on If Differ	ent From	m Surface	TI			
UL or lot no.	Section	Township	Range	Lot. Idn	Feet from	the North/S	outh Line	Feet from the	East/West line	County		
· · · · · · · · · · · · · · · · · · ·		⁹ Proposed	Pool 1					¹⁰ Proposed Po	pol 2			
EUNI	CE MONUM	ENT; GRAD	BURG - SA	N ANDRES								
<u>. </u>			<u> </u>			•						
11 Work T			¹² Well Type C	ode	¹³ Cable							
¹⁶ Mu	D Itiple		O 17 Proposed De	-4	R P nation ¹⁹ Contractor				508.2'			
	NO		4500'	pin		nation ¹⁹ Contractor ²⁰ Spud Date SAN ANDRES NABORS 6/20/02						
·				Proposed		d Cement P	1					
Hole S	ize	Cas	ing Size	Casing we		Setting De		Sacks of Cemer	nt Est	timated TOC		
11					24							
		8-5/8		15.5		1225 3850				SURFACE		
7-7/8 5-			-1/2	15	.5	3850				SURFACE		
	· · · · · · · · · · · · · · · · · · ·											
	·											
						K, give the data	on the pre	esent productive zor	ne and proposed n	ew productive zone.		
Describe the blow	-	• •	•		-							
Drill to 45	00', cem	ent a 3-1	l/2' liner	from 3700)'-4500' ;	and test th	e lower	Grayburg & S	an Andres zo	ones.		
			 	Permit Exp	pires 1 N	fear Frem	A.S. M.			2.		
Permit Expires 1 Your From Approval (2) J. 2 L'ate Unless Drillin g Underway Deepehine (2) K- Tours												
					D	eepehin	iç	\	is ti	ូម ^{ស្តុ}		
23		· · · · ·					 0f	HEINAL SIGN	the .			
²³ I hereby certify that the information given above is true and complete to the						OIL CONSERV ATION ON ISION						
best of my knowledge and belief.						Approved by:						
Signature: UMY /. Spang												
Printed name: AMY T. SPANG						Title:						

best of m Signature:	y knowledge and belief.	<i>Xpana</i>	Approved by:					
Printed na	ume: AMY T. SPANG							
Title:	REG. COMPLIANC	e analyst	Approval Date: Expiration Date:					
Date:		Phone:	Conditions of Approval: 200	12				
6/13/02		281/366-7655	Attached					

District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

٦,

State of New Mexico Energy, Minerals & Natural Resources Department OIL CONSERVATION DIVISION 1220 South St. Francis Dr. Santa Fe, NM 87505 Form C-102 Revised August 15, 2000 Submit to Appropriate District Office State Lease - 4 Copies Fee Lease - 3 Copies

AMENDED REPORT

		W	ELL LC	DCATIO	N AND ACR	EAGE DEDIC	ATION PLA	Т		
'API Number 30-025-27254				² Pool Code		³ Pool Name				A
30-02	-5~2	125		23000 Evnice Monument, Grayburg - San An					Andres	
Property Code			٨	⁵ Property Name					Well Number	
294	5		<u> </u>	lue F.	Lurry					~
		0	0 1		⁸ Operator	Δ				Elevation
00077	18	<u></u> B	<u>P AME</u>	erica f	roduction	n Company			35	08. Z'GR
	¹⁰ Surface Location									
UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/	West line	County
B	2	21S	37E		660	North	1980	Eas.	f	Lea
¹¹ Bottom Hole Location If Different From Surface										
UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/	West line	County
12 Dedicated Acres	¹² Dedicated Acres ¹³ Joint or Infill ¹⁴ Consolidation Code ¹⁵ Order No.									
40										

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

16	-039 04 41	1980'	¹⁷ OPERATOR CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief. My 7. Spung Signature
			Appy T. Spang Printed Name Regulatory Compliance traject a18: G/ 13/ 02 Date 18: SURVEYOB GERTIFICATION
			I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.
			Signature and Seal of Professional Surveyor:

EXHIBIT 1

DRILLING OPERATIONS CLASS -1: NORMAL PRESSURE < 10PPG OPTION - 2: MMS STANDARD; SINGLE SIZE DRILL STRING





BLOWOUT PREVENTION EQUIPMENT SPECIFICATIONS

- 1. All BOP equipment shall be fluid and/or mechanically operated.
- 2. BOP's and all fittings will be in good working condition.

•

- 3. Equipment through which the bit must pass shall be at least as large as the casing size being drilled.
- 4. The nipple above the BOP shall be at least the same size as the last casing set.
- 5. The upper kelly cock with handle and lower kelly cock shall be rated at the BOP working pressure.
- 6. A floor safety valve (full opening) or drill string BOP with appropriate pressure ratings shall be available on the rig floor with connections or subs to fit any tool joint in the string.
- 7. The minimum size choke line shall be 3 inches nominal diameter, with a minimum size for vent lines downstream of chokes of 2 inches nominal, and vent lines which by-pass shall be a minimum of 3 inches nominal and as straight as possible.
- 8. All valves, fittings and lines between the closing unit and the blowout preventer stack should be of steel construction with rated working pressure at least equal to working pressure rating of the stack. Lines shall be bundled and protected from damage.
- 9. Minimum size for kill line is 2 inches nominal.
- 10. Ram type preventers shall be equipped with extension hand wheels or hydraulic locks.

