NO. SPE COPIES RECEIVED DISTRIBUTION SANTA FE FILE U.S.G.S.	NEW	MEXICO OIL CONSER	RVATION COMMISSION	Form C-101 Revised 1-1- SA, Indicat	25-27504 65 Type of Lague
LAND OFFICE OPERATOR	DN FOR PERMIT TO	DRILL DEEPEN (	DR PLUG BACK		
In. Type of Work				7. Thu A n	ent flane
b. Type of Well DRILL		DEEPEN	- ~PLUG B	ACK	0.000
CIL GAS WELL	) 0∵H£R		SINGLE MULT		ell (NCT-E)
2. Mane of Cryptor	- •			9. Well 1.c.	······································
Gulf Oil Corp	oration	······································			Herel, or William
	, Hobbs, NM 8	8240		Hardy	Drinkard Blinebry
	ER LOC	ATED 370 FE	ET FROM THE NORT	h_LINE	11 Joseph Kirks
0010	11. o. tr	11			HANNAXEN )
442 2310 FEET FROM			215 865. 36		
ΔΗΠΗΠΗΠΗΝ				Lea	
			. Projesed Depth 19	A. Formation	
				inebry & Drinka	L. Hirry of C.T.
11. Elevations (Show whether DF	( <i>Kl</i> , etc.) 21A. Kind	& Status Plug. Bend 21	B. Drilling Contractor		Date Work will stort
3538.7' GL			Undetermined		9-1-81
23.	P	ROPOSED CASING AND	CEMENT PROCEAM		· · · · · · · · · · · · · · · · · · ·
	• ··	•			· · · · · · · · · · · · · · · · · · ·
SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
<u> </u>	<u> </u>	48# 36#	2800'	<u>400</u> 700	circ circ
8-3/4"	7"	26#&23#	6900'	700	2800'
	<b>f</b> 1	i i	l		
Drilling Mud:	0' - 3 350' - 2 2800' - 6				
See Attached	BOP Drawing #2	•			
`					
				AL VALID FOR 180	DAYS
			PERMI	T EXPIRES 121	T82
				SS DRILLING UNDE	RWAY
N ABOVE SPACE DESCRIBE PR	OPOSED PROGRAM; IF P	ROPOSAL IS TÔ DEEPEN OR	PLUG BACK, GIVE DATA ON F	RESENT PRODUCTIVE ZONE	AND PROPOSED NEW PRODUC
hereby certify that the informatic	er program, if any.	eto to the Kana of multi-	wind a and batter	· · · · · · · · · · · · · · · · · · ·	
intervention of the information	a bove is true and compl		-		
figned <u><u>L'</u>(; Ulu</u>	diam	Title Area Pro	duction Manager	Date7-2	7-81
(This space for S	State Use)	SUPARV	SOR DISTRIC	<b>ŕ i</b>	1984
IPPROVED BY	alif-	TITLE		DATE	
ONDITIONS OF APPROVAL, IF	ANY				

¢







The blowout preventer assembly shall consist of one blind ram preventer and one pipe ram preventer, both hydraulically operated; a Shaffer Tool Works stripper; valves ; chokes and connections, as illustrated. If a topered drill string is used, a ram preventer must be provided for each size of drill pipe. Casing and tubing rams to fit the preventers are to be available as needed. The ram preventers may be two singles or a double type. If correct in size, the flanged avilets of the ram preventer may be used for connecting to the 4-inch I.D., choke flow line and kill line. The substructure height shall be sufficient to install a rotating blowout preventer.

the pressure-operated devices simultaneously within \_\_\_\_\_scoonds. The pump (s) is to be connected to a closed type hydraulic operating system. (2) <u>When requested</u>, accumulators with a precharge of nitrogen of not less than 750 PSI and connected so as to receive a fluid charge from the above pump (s). With the charging pump (s) shut down, the pressurized fluid volume stored in the accumulators must be sufficient to close all the pressurecapabilities. lent, is to be available to operate the above pump (s); or there shall be an additional pump (s) operated by separate power and equal in performance operated devices simultaneously within Minimum operating equipment for the proventers shall be as follows: (1) Pump (s), driven by a continuous source of power, capable of closing all remaining accumulator fluid volume at least seconds; after closure, the remaining accumulator pressure shall be not less than 1000 PSI with the rest\_\_\_\_percent of the original. (3) <u>When requested</u>, an additional source of power, remote and equiva-

The closing manifold shall have a separate control for each pressure-operated device. Controls are to be labeled, with control handles indicating open and closed positions. A pressure reducer and regulator must be provided if a Hydril preventer is used. Gulf Legion No. 33 hydraulic oil, an equivalent or better, is to be used as the fluid to operate the hydraulic equipment.

choke lines shall be constructed as straight as possible and without sharp bends. Easy and safe access is to be maintained to the choke manifold. All valves are to be selected for operation in the presence of ail, gas, and drilling fluids. The choke flow line valve connected to the drilling spool and all run type preventers must be equipped with stem extensions, universal joints if needed, and hand wheels which are to extend beyond The choke manifold, choke flow line, and choke lines are to be supported by metal stands and adequately anchored. The choke flow line and the edge of the derrick substructure. All other valves are to be equipped with handles.





DRAWING NO. 2

## NEW T XICO OIL CONSERVATION COMMISSION WELL LUDATION AND ACREAGE DEDICATION F. T

-

.

.....

Form C-102 Supersedes C-128 Elfective 14-65

	All distances :	must be from the outer boundaries of the S	ection.	
operator		Lease	W=11 71	0.
GULF OIL CO		R.R. BELL NC		4
C 11		JTH 36 EAST	LEA	
Actual Footage Location of We 370	NODTU	line and 2310 feet from	the WEST Har	
1441 1101	n ine LIURLIA	line and 2310 feet from Pool	Dedicat+1 Acr	-0/2#*
3538.7	Blinebry & Drinkar	rd Hardy Drinkard & H	lardy Blinebry	40 Acres
	lease is dedicated to a	ject well by colored pencil or had the well, outline each and identify		
	ization, unitization, forc	whip is dedicated to the well, have re-pooling. etc? ' type of consolidation	the interests of all owners	been consoli-
this form if necess No allowable will b	ary.) be assigned to the well u	et descriptions which have actual until all interests have been conso standard unit, eliminating such int	olidated (by communitization,	. unitization,
	-370	s l	CERTIFICAT	10N
2310'	δ		I hereby certify that the tained herein is true and best of my knowledge and for the tained herein is true and best of my knowledge and the tained here tails and the tail tails and tails	complete to the
			R. C. Anderson Position Area Productio Company	n Manager
		     	Gulf Oil Corpo	racion
		A. P. L. K. IA. ROMAN D. M. KINI ME KICO P.	I hereby certify that th shown on this plat was pi notes of actual surveys under my supervision, an is true and correct to knowledge and belief.	latted from field made by me ar id that the same
		TODOS AND SURF	Date Surveyed 7-27- Registered Protessional En and/or Land Surveyor	
. 1			II ST late	

