

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

N. M. OIL CONS. COMMISSION
P.O. BOX 1000
TUCSON 85724

SUBMIT IN TRIPPLICATE
(Other instructions on reverse side)
HUDD, NEW MEXICO

Form approved.
Budget Bureau No. 42-R1424.
LEASE DESIGNATION AND SERIAL NO.

NM 14490

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Gulf Oil Corporation	8. FARM OR LEASE NAME Chaney Federal
3. ADDRESS OF OPERATOR P. O. Box 670, Hobbs, NM 88240	9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980' FNL & 1980' FWL	10. FIELD AND POOL, OR WILDCAT Wildcat
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 35-T21S-R32E	12. COUNTY OR PARISH Lea
13. STATE NM	
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3675' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Casing

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Cactus Spudded 12 1/2" hole at 7:00 A.M., 11-18-81; TD 4:00 P.M., 11-18-81. RU and ran 12 joints 8-5/8" 24# K-55 ST&C (547') set at 500'. Cement with 310 sacks Class "C" with 2% CaCl. Plug down 9:45 P.M., 11-18-81. Circulate cement to surface. WOC 18 hours. Test casing. Drill cement float and shoe.

RECEIVED
DEC 08 1981

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWEIL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED *[Signature]*

TITLE Area Drilling Superintendent DATE 12-7-81

(This space for Federal or State office use)

DEC 11 1981

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

U.S. GEOLOGICAL SURVEY
ROSWEIL, NEW MEXICO

*See Instructions on Reverse Side