

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 17252

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

LLANO FEDERAL

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

SAND HILLS GRAYBURG

SAN ANDRES

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

12. COUNTY OR PARISH

LEA

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

MINERALS, INC.

3. ADDRESS OF OPERATOR

P. O. Box 1320, Hobbs, New Mexico, 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1,650 FSL, 330' FEL Sec. 31, T20S, R39E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3,560.8 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

REPAIR WELL

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☐
☒

Subsequent Report


(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12/24/81 Set surface casing as follows:
Set at 1,651' 8-5/8, 24# J-55
cemented with 550 SX Halliburton light
followed with 200 SX Cl. "C" neat.
Bumped plug at 10:06 A.M. 12-24-81.
Circulated 230 SX. USGS notified 12-23-81.

1/12/82 Set production casing as follows:
Set at 4,435', 5 1/2", 15.5# J-55 csg.
Cement with 300 SX. Cl. "C" with 6# salt
and .3% Halad-4.
Float held. Rig released 6:00 P.M.

1/13/82 WO Completion Unit.



U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE: President and CEO

DATE

1/27/82

FOR RECORD
(This space for Federal or State office use)

ROGER A. CHAPMAN

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

FEB 16 1982

TITLE

DATE

U.S. GEOLOGICAL SURVEY See Instructions on Reverse Side