

N. M. OIL CONS. COMMISSION
P. O. BOX 198
HOBBS, NEW MEXICO 88240
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR

Alpha Twenty-One Production Company

3. ADDRESS OF OPERATOR

P.O. Box 1206, Jal, NM 88252

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 660 FNL - 380 FEL, Sec. 17, T-20-S, AT SURFACE: R-39-E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☒
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE

NM 17252

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Colvin Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 17, T-20-S, R-39-E

12. COUNTY OR PARISH 13. STATE

Lea

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3539' GL

(NOTE: Report results of multiple completion or zone change on Form 9-331-C)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Our intention is to plug the well as follows:

- (1) 150' plug, 75' above & 75' below San Andres (4225-4375) w/50 sx Cl. C
- (2) 150' plug, 75' above & 75' below Queen (3314-3464) w/50 sx Cl. C
- (3) 150' plug, 75' above & 75' below Yates/7-Rivers (2814-2964) w/50 sx Cl. C
- (4) 100' plug, 50' above & 50' below Base Salt (2695-2795) w/35 sx Cl. C
- (5) 100' plug, 50' above & 50' below Guide Shoe (962-1062) w/35 sx Cl. C
- (6) Surface plug of 15 sx Class "C" cement.

Subsurface Safety Valve: Manu. and Type

Set @

Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Michael D. Oney
Michael D. Oney

TITLE Drill. Supt.

DATE 1-31-84

APPROVED

(This space for Federal or State office use)

APPROVED BY (Orig. & 5d.) PETER W. CHESTER

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

FEB 22 1984

RECEIVED

FEB 24 1984

O.C.D.

100-100000