

0+5 - USGS -P.O. Box 1857
Roswell, NM 88201

1-Engr. RH
1-Foreman CRM

1-File

8-WIOs

Form 9-331
Dec. 1973

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒
well well other

2. NAME OF OPERATOR
Getty Oil Company

3. ADDRESS OF OPERATOR
P.O. Box 730, Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: Ltr. K, 1980' FSL & 1980' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

☒
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE
14331

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Bilbrey 29 Fed Com

9. WELL NO.
1

10. FIELD OR WILDCAT NAME
Bilbrey Basin Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 29, T21S, R32E

12. COUNTY OR PARISH
Lea

13. STATE
NM


14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3682.4 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4/23/82 Drilled 12 1/4" hole at 4583'. Ran & set 50 jts. (2212') of 9 5/8 S-80 36# 8rd ST&C range 3 A cond. csg. + 59 jts. (2347') 9 5/8 H-40, 32.3# 8rd ST&C R-3 A cond. csg. & set at 4583'. By Howco cemented 9 5/8" csg. using 3000 sxs of Hal-lite, 15# salt, 5# gilsonite, 1/4# flocele & 250 sxs Hal-Class "C" 1/4# flocele. Circulated 500 sxs to pit.
4/24/82 W.O.C. 18 hours.
4/25/82 Installed CIW 10", 5000# head & 7 pressure tested csg. to 1500#. OK.
4/26/82 Drlg. 8 1/2" hole at 4790' in lime & sand.



Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Don C. Smith TITLE Area Superintendent DATE May 7, 1982

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

MAY 20 1982
U.S. GEOLOGICAL SURVEY
POSWELL, NEW MEXICO