O+5 - USGS - P.O Box 1857 Roswell, I. 88201	7	M L - File	<pre>1 - Eng. Tech 1 1 - Laura Richard</pre>				
	P. H. 05 9200 080		Midland				
orm 9–331 Dec. 1973	Latinary & Rama & Western		n Approved. get Bureau No. 42–R1424				
UNITED STATES		5. LEASE					
DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9–331–C for such proposals.)		14331 6. IF INDIAN, ALLOTTEE OR TRIBE NAME 7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME Bilbrey 29 Fed. Com.					
				1. oil gas 🔀 other		9. WELL NO.	
				2. NAME OF OPERATOR		1	
				Getty Oil Company		10. FIELD OR WILDCAT NAME Bilbrey Basin Morrow	
3. ADDRESS OF OPERATOR							
P.O. Box 730 Hobbs, NM 88240 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: Ltr. K, 1980' FSL & 1980' FWL AT TOP PROD. INTERVAL:		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA					
		Sec. 29, T21S,					
		12. COUNTY OR PARISH	i				
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:		Lea 14. API NO.	NM				
6. CHECK APPROPRIATE BOX TO IN	DICATE NATURE OF NOTICE,	14. API NO.					
REPORT, OR OTHER DATA		15 ELEVATIONS (SHOWN 3682.4 GR	V DF, KDB, AND WD)				
REQUEST FOR APPROVAL TO: STEST WATER SHUT-OFF	SUBSEQUENT REPORT OF:						
RACTURE TREAT	The second provided in	The second secon					
SHOOT OR ACIDIZE REPAIR WELL							
PULL OR ALTER CASING		change on Form 9	nultiple completion or zone -330.)				
MULTIPLE COMPLETE CHANGE ZONES		1 1382					
ABANDON*			•				
(other) Spud	<u> </u>						
17. DESCRIBE PROPOSED OR COMPLE including estimated date of starting measured and true vertical depths for	TED OPERATIONS (Clearly stage any proposed work. If well is	te all pertinent details, an directionally drilled, give su	d give pertinent dates, bsurface locations and				
4/7/82 Sharp Drilling Co. hole @ 5:30 P.M.	. Rig #36 moved in an	d rigged up. Spud	ded 17 1/2"				
	ole to 500'. Ran 11						
	et @ 500'. Homco cem w/2% CaCl. Circulate		using 500 sxs.				
	•						
	WOC 18 hours. Pressured up on casing to 1200#. OK. Drilling 12 1/4" hole @ 2250' in salt & anhydrite						
Subsurface Safety Valve: Manu. and Tyne	e	Se	t @ Ft.				
\wedge			t @ Ft.				
Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is SIGNED	true and correct						
18. I hereby certify that the foregoing is	true and correct Area Engr	nterdente Apri ACCEPTED F					
18. I hereby certify that the foregoing is SIGNED Abnal f. Officience for Dale R Crockett	true and correct Area Engr TITLE Area Superi (This space for Federal or State o	nter.dente Apri ACCEPTED F					
18. I hereby certify that the foregoing is SIGNED Abnal f. Ollinse for Dale R. Crockett	true and correct Area Engr	ntendente ACCEPTED F					

ROSWELL, NEW MEXIC