

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

OIL CONSERVATION DIVISION

DISTRICT I
P.O. Box 1980, Hobbs NM 88241-1980

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO.

30-025-27827

5. Indicate Type of Lease

STATE ☐

FEE ☐

6. State Oil & Gas Lease No.

LG-1145

7. Lease Name or Unit Agreement Name

Comanche State Unit

8. Well No.

4

9. Pool name or Wildcat

North Legg (Delaware)

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☐

OTHER Dry Hole

2. Name of Operator

Enron Oil & Gas Company

3. Address of Operator

P.O. Box 2267 Midland, TX 79702

4. Well Location

Unit Letter H : 1980 Feet From The North Line and 660 Feet From The East Line

Section 9 Township 21S Range 33E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3840.4' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 1) Set CIBP @ 8600' + 35' of cement on top.
- 2) Back off and pull approximately 6000' of 5-1/2" casing.
- 3) Set 100' cement plug across 5-1/2" casing stub. 50' in and 50' out at approximately 5950' to 6050'.
- 4) Set cement plug from 5571' to 5671'. 50' in and 50' out of 9-5/8" casing. Tag cement plug with tubing.
- 5) Set 100' cement plug from 2521' to 2621'.
- 6) Set 60' cement plug from surface to 60'.
- 7) Install dry hole marker. Clean and restore location.

See attached well diagram.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

M. Lee Roark

TITLE

Engineer Tech.

DATE

12/17/99

TYPE OR PRINT NAME

M. Lee Roark

TELEPHONE NO. 915/686-3608

(This space for State Use)

APPROVED BY

CHRIS WILLIAMS
SUPERVISOR

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

IC

PROPOSED P&A
WELL SCHEMATIC