

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

3a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
LG-1145	

SUNDRY NOTICES AND REPORTS ON WELLS
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.

1. OIL <input type="checkbox"/> WELL GAS <input type="checkbox"/> WELL OTHER- Dry		7. Unit Agreement Name
2. Name of Operator Gulf Oil Corporation		8. Farm or Lease Name South Lynch
3. Address of Operator P. O. Box 670, Hobbs, NM 88240		9. Well No. 1
4. Location of Well UNIT LETTER H 1980 FEET FROM THE North LINE AND 660 FEET FROM THE East LINE, SECTION 9 TOWNSHIP 21S RANGE 33E NMPM.		10. Field and Pool, or Wildcat Bone Springs
15. Elevation (Show whether DF, RT, GR, etc.) 3300' GL		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

POH with tubing. Cap CIBP at 9610' with 35' cement. Set CIBP at 9330', cap with 35' cement. Cut casing at 8855', POH with casing. Tag fill. Pump 75 sacks cement at 8928'. Flush cement with 35 bbls mud; hole circulated during flush. Spot 50 sacks Class "H" neat 7555'-7455'. Spot 75 sacks Class "H" neat 5676'-5530'. Circulate. Spot 40 sacks cement 4120'-4020'. Spot 40 sacks cement 3650'-3550'. Spot 40 sacks cement 601'-501'**. Dig out cellar. Cut off spool. Surface had plate welded on with cement on top; OCD gave permission to leave surface as is. Spot 20 sack surface plug. Install dry hole marker. Clean and clear location. P&A 3-6-83.

** Not required to tag per Tony Plattsmier.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.		
SIGNED <u>W. J. Simpson</u>	TITLE <u>Area Engineer</u>	DATE <u>3-7-83</u>
APPROVED BY <u>A. Plattsmier</u>	TITLE <u>OIL & GAS INSPECTOR</u>	DATE <u>JUN 20 1983</u>
CONDITIONS OF APPROVAL, IF ANY:		