DISTRIBUTION	Ī	
SANTA FE		
FILE		
U.1.0.1.		
LAND OFFICE		
OPERATOR	1	1

WIL CONSERVATION DIVISION P. O. BOX 2088

Form C-103 Revised 10-1-78

SANTA FE, NEW MEXICO 87501		
FILE	5a. Indicate Type of Lease	
U.S.O.S.	State X For	
OPERATOR	5. State Oti & Gas Lease No.	
· · · · · · · · · · · · · · · · · · ·	LG-1145	
SUNDRY NOTICES AND REPORTS ON WELLS		
IDO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEFPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)		
11.	7, Unit Agreement Name	
OIL COTHER Dry		
12. Name of Operator	8. Form or Lease Hame	
Gulf Oil Corporation	South Lynch	
P. O. Box 670, Hobbs, NM 88240	7 . Well No.	
14. Location of Well	10. Field and Pool, or Wildcat	
	· ·	
UNIT LETTER H . 1980 FEET FROM THE NORTH LINE AND 660 PEET FROM	TITTITITITITITITITITITITITITITITITITIT	
THE East LINE, SECTION 9 TOWNSHIP 21S MANGE 33E NAMPM.		
THE LOSE LINE, SECTION TOWNSHIP 210 RANGE JUL NAMPH.		
15. Elevation (Show whether DF, RT, GR, etc.)	12. County	
3300 GL	Lea	
		
Check Appropriate Box To Indicate Nature of Notice, Report of Ut		
NOTICE OF INTENTION TO: SUBSEQUENT	REPORT OF:	
PERFORM REMEDIAL WORK PLUG AND ABANDON X REMEDIAL WORK	. ALTERING CASING	
TEMPORARILY ABANDON PULL OR ALTER CABING CHANGE PLANS CASING TEST AND CEMENT JOB	PLUG AND ABANDOHMENT	
PULL OR ALTER CABING CHANGE PLANS CASING TEST AND CEMENT JQB		
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including	estimated date of starting any proposed	
work) SEE RULE 1103.		
Circulate hole with abandonment mud. Spot 35' Class "H" neat cemer	it cap on CIBP	
at 9610'. Set CIBP at 9330', cap with 35' cement. Cut casing at f	ree point depth.	
POH with casing and tubing. Spot 100' Class "H" neat cement plugs	as follows:	
99271 90271		
8827'-8927' with 90 sacks		
7455'-7555' with 75 sacks		
** 5530'-5671' with 90 sacks		
. 4020'-4120' with 40 sacks		
3550'-3650' with 40 sacks	•	
1700'-1800' with 40 sacks		
Joi out with 40 Sacks		
0'-50' with 20 sacks (surface plug)		
These will be tagged per OCD request. Class "H" cement plug will be	ant narosa 51.11	
casing stub; if stub is close to any of the above plugs, cement will	he adjusted to	
cover 50' into the stub. The $5\frac{1}{2}$ " casing stub plug will be tagged pe	. De adjusted to	
cover 30 Thro the stub. The 32 casing stub plug will be tagged pe	er och request.	
Set dry hole marker. Clean and clear location.		
bee dry note marker. Great and creat location.		
24 HOUR NOTIFICATION IS REQUIRED		
18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.		
Area Engineer	DATE 1-26-83	
OIL & GAS INSPECTOR		
ORIGINAL SIGNED BY	MATE JAN 28 1983	
APPROVED BY EDDIE W. SEAY	- "" - UMH WU - IUUU	