

## OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input checked="" type="checkbox"/>	GAS WELL <input type="checkbox"/>	OTHER <input type="checkbox"/>
Name of Operator Alpha Twenty-One Production Company		
Address of Operator P.O. Box 1206, Jal, NM 88252		
Location of Well UNIT LETTER <u>P</u> <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>990</u> FEET FROM THE <u>East</u> LINE, SECTION <u>21</u> TOWNSHIP <u>21-S</u> RANGE <u>37-E</u> NMPM.		
15. Elevation (Show whether DF, RT, GR, etc.) 3432.5' GL		
12. County Lea		

## Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

## NOTICE OF INTENTION TO:

FORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
ALTER OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

## SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPERATIONS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <u>Casing and Cementing</u> <input checked="" type="checkbox"/>

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

The well was spudded 7-12-82.

Drilled 15" hole and set 30' of 12-3/4" Grade B Conductor Pipe and cemented with Redimix to surface.

Drilled 12-1/2" hole and set 402.29' of 8-5/8", 23#, Grade B Surface Casing and cemented with 275 sx Class "C", CAC12. Circulated 100 sx. (Work accomplished 7-12-82)

Drilled 7-7/8" hole and set 4247.78' of 5-1/2", 15.50#, Production Casing as follows:

Guide Shoe	.80'
Shoe jt.	40.01'
Float collar	1.65'
106 jts.	4205.32'
Total	4247.78'

## Cement:

Lead Slurry--650 sx Halliburton Lite.

Tail Slurry--350 sx 50/50 Poz "C". Circulated 70 sx. (Work accomplished 7-20-82)

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Robert W. Lenoferd

TITLE V.P./Energy ResourcesDATE 7-21-82

ORIGINAL SIGNED BY

APPROVED BY ADVISORY SECTION

TITLE \_\_\_\_\_

DATE JUL 23 1982

CONDITIONS OF APPROVAL, IF ANY, SUPPL.