

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Fee ☐
3. State Oil & Gas Lease No.
LG-1022

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Amoco Production Company	8. Farm or Lease Name State DV
3. Address of Operator P. O. Box 68, Hobbs, New Mexico 88240	9. Well No. 1
4. Location of Well UNIT LETTER L, 1980 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 34 TOWNSHIP 21-S RANGE 35-E N.M.P.M.	10. Field and Pool, or wildcat Wildcat Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 3691.9' GL	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER <input type="checkbox"/>		drilling update	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to a total depth of 10,775'. On 3-6-83, ran 7-5/8", 39#, 33.7#, and 39# S-95 casing. Casing was set at 10,775'. DV tool at 7474'. Cemented first stage with 475 sx lite and 400 sx class H. Plugged down. Opened stage tool and circulated 44 sx cement to pit. Circulated 6 hr. and cemented second stage with 650 sx lite with additives and tail-in 400 sx class H. Plugged down. WOC. Top of cement at 1760' by temperature survey. Drilled out cement, DV tool, float collar, and cement. Pressure tested casing at 1000 for 30 min.- OK. Reduced bit to 6-1/2" and resumed drilling.

0+4-NMOCD,H 1-HOU 1-W. Stafford, HOU 1-CMH 1-Superior, Midland

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Charles M. Herrin TITLE Assist. Admin. Analyst DATE 3-8-83

ORIGINAL SIGNED BY JERRY SEXTON

APPROVED BY DISTRICT SUPERVISOR TITLE DATE MAR 10 1983

CONDITIONS OF APPROVAL, IF ANY: