

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
CONOCO INC.
3. ADDRESS OF OPERATOR
P. O. Box 460, Hobbs, N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FSL + 2100' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF ☐ ☐
FRACTURE TREAT ☐ ☒
SHOOT OR ACIDIZE ☐ ☒
REPAIR WELL ☐ ☐
PULL OR ALTER CASING ☐ ☐
MULTIPLE COMPLETE ☐ ☐
CHANGE ZONES ☐ ☒
ABANDON* ☐ ☐
(other) ☐ ☐

5. LEASE
LC - 032096 (B)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
NMFU

8. FARM OR LEASE NAME
LOCKHART B-13A

9. WELL NO.
9

10. FIELD OR WILDCAT NAME
WANTZ ABO / DRINKARD

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SEC. 13, T-21S, R-37E

12. COUNTY OR PARISH
LEA

13. STATE
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED
JAN 5 10 50 AM '84
OIL & GAS
DIVISION
SANDOZ

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRU 11/3/83. SET RBP @ 6920'. SPOTTED 5 BBLs 15% HCL-NE-FE @ 6890'. PERF w/ 1 JSPF @ 6704', 18', 58', 62', 87', 6817', 29', 54', + 6873'. SET RBP @ 6905' + PKR @ 6593'. PMPD 18 BBLs 15% HCL-NE-FE. ACID FRAC'D w/ 162 BBLs GELLED PAD + 122 BBLs 28% HCL-NE-FE. FLUSHED w/ 50 BBLs TFW. SWBD. REL PKR + RESET RBP @ 6700'. SPOTTED 5 BBLs 15% ACID @ 6650'. PERF w/ 1 JSPF @ 6578', 82', 86', 92', 95', 6605', 15', 36', 39', 43', 48', 51', + 6656'. SET PKR @ 6450'. PMPD 28 BBLs 15% ACID. ACID FRAC'D w/ 200 BBLs 28% HCL-NE-FE + 381 BBLs GELLED TFW. SWBD. REL PKR + RBP. 9 BO, 5 BW, 10 MCF 12/3/83

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Wm. A. Butterfield Administrative Supervisor DATE 1/3/84

ACCEPTED FOR RECORD (This space for Federal or State office use)

APPROVED BY PETER W. CHESTER TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:
MAR 1 1984