## STATE OF NEW MEXICO SHERGY AND MINERALS DEPARTMENT

NO. OF COPIES ACCEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

## OIL CONSERVATION DIVISION

DISTRIBUTION	P. O. BOX 2088	Revised 10-1-78
SANTA FE	SANTA FE, NEW MEXICO 87501	
FILE	· ·	5a. Indicate Type of Lease
U.S.O.S.		State X Fee
LAND OFFICE		5. State Oil 6 Gas Lease No.
OPERATOR	· ·	
		A-1375
SUL	DRY NOTICES AND REPORTS ON WELLS	
IDO NOT USE THIS FORM FOR	PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR CATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)	·
	CASION FOR FERMING TO WORK CATOLY FOR SUCH FROPESTICALLY	7, Unit Agreement Name
OIL [▼] 6A8 [¬]		
WELL X WELL WELL	OTHER.	
Name of Operator		8. Farm or Lease Name
ME-TEX SUPPLY COM	PANY	Wallace State
. Address of Operator		9. Well No.
	DDC NEW MEYTON 999/A	10
	OBBS, NEW MEXICO 88240	10. Field and Pool, or Wildcat
1. Location of Well		
N N	3630 FEET FROM THE SOUTH LINE AND 1650	PEET FROM UNDESIGENATED
UNIT CETTER		
Most	ECTION 3 TOWNSHIP 21S RANGE 36E	
THE WEST LINE, S	CCTION TOWNSHIP Z TO RANGE DUS	— umom. ///////////////////////////////////
mmmmm	THE STATE OF	12. County
	15. Elevation (Show whether DF, RT, GR, etc.)	12. County
	3537.9' GR	
it. Cho	ck Appropriate Box To Indicate Nature of Notice, Repo	er or Other Data
	· · · · · · · · · · · · · · · · · · ·	
NOTICE O	F INTENTION TO: SUBS	EQUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON	COMMENCE DRILLING OPHS.	PLUG AND ABANDONMENT
	CHANGE PLANS CASING TEST AND CEMENT JQ	X
FULL OR ALTER CASING		
	OTHER	
OTHER	•	
	Charles and all participated and also participated asset	including estimated date of starting any proposed
17, Describe Proposed or Complete	od Operations (Clearly state all pertinent details, and give pertinent dates	, including estimated date of starting any proposed
	od Operations (Clearly state all pertinent details, and give pertinent dates	, including estimated date of starting any proposed
17. Describe Proposed or Complete work) SEE RULE 1103.		
17. Describe Proposed or Complete	Ran 175jts. $5\frac{1}{2}$ " 17# & 15.5#/', seamless, H-	40, 8rd thread, ST&C, new
17. Describe Proposed or Complete work) SEE RULE 1103.	Ran 175jts. $5\frac{1}{2}$ " 17# & 15.5#/', seamless, H-production casing, total 7028.96', set @ 70	40, 8rd thread, ST&C, new 07'. Cemented w/ 1510sx
17. Describe Proposed or Complete work) SEE RULE 1103.	Ran 175jts. $5\frac{1}{2}$ " 17# & 15.5#/', seamless, H-production casing, total 7028.96', set @ 70 Pace-setter Lite w/ 10#/sk salt, $\frac{1}{4}$ #/sk cell	40, 8rd thread, ST&C, new 07'. Cemented w/ 1510sx o-seal, 5#/sk gilsonite
17. Describe Proposed or Complete work) SEE RULE 1103.	Ran 175jts. 5½" 17# & 15.5#/', seamless, H-production casing, total 7028.96', set @ 70 Pace-setter Lite w/ 10#/sk salt, ¼#/sk cell + 300sx Class "C" neat cement. Circulated	40, 8rd thread, ST&C, new 07'. Cemented w/ 1510sx o-seal, 5#/sk gilsonite approximately 140sx cement
17. Describe Proposed or Complete work) SEE RULE 1103.	Ran 175jts. $5\frac{1}{2}$ " 17# & 15.5#/', seamless, H-production casing, total 7028.96', set @ 70 Pace-setter Lite w/ 10#/sk salt, $\frac{1}{4}$ #/sk cell	40, 8rd thread, ST&C, new 07'. Cemented w/ 1510sx o-seal, 5#/sk gilsonite approximately 140sx cement
17. Describe Proposed or Complete work) SEE RULE 1103.  01/01/83	Ran 175jts. $5\frac{1}{2}$ " 17# & 15.5#/', seamless, H-production casing, total 7028.96', set @ 70 Pace-setter Lite w/ 10#/sk salt, $\frac{1}{4}$ #/sk cell + 300sx Class "C" neat cement. Circulated to surface. Bumped plug w/ 2500psi. Plug	40, 8rd thread, ST&C, new 07'. Cemented w/ 1510sx o-seal, 5#/sk gilsonite approximately 140sx cement down 3:48PM 01/01/83.
17. Describe Proposed or Complete work) SEE RULE 1103.	Ran 175jts. 5½" 17# & 15.5#/', seamless, H-production casing, total 7028.96', set @ 70 Pace-setter Lite w/ 10#/sk salt, ½#/sk cell + 300sx Class "C" neat cement. Circulated to surface. Bumped plug w/ 2500psi. Plug Tested 5½" production casing w/ 1200psi for	40, 8rd thread, ST&C, new 07'. Cemented w/ 1510sx o-seal, 5#/sk gilsonite approximately 140sx cement down 3:48PM 01/01/83.
17. Describe Proposed or Complete work) SEE RULE 1103.  01/01/83	Ran 175jts. $5\frac{1}{2}$ " 17# & 15.5#/', seamless, H-production casing, total 7028.96', set @ 70 Pace-setter Lite w/ 10#/sk salt, $\frac{1}{4}$ #/sk cell + 300sx Class "C" neat cement. Circulated to surface. Bumped plug w/ 2500psi. Plug	40, 8rd thread, ST&C, new 07'. Cemented w/ 1510sx o-seal, 5#/sk gilsonite approximately 140sx cement down 3:48PM 01/01/83.
17. Describe Proposed or Complete work) SEE RULE 1103.  01/01/83	Ran 175jts. 5½" 17# & 15.5#/', seamless, H-production casing, total 7028.96', set @ 70 Pace-setter Lite w/ 10#/sk salt, ½#/sk cell + 300sx Class "C" neat cement. Circulated to surface. Bumped plug w/ 2500psi. Plug Tested 5½" production casing w/ 1200psi for	40, 8rd thread, ST&C, new 07'. Cemented w/ 1510sx o-seal, 5#/sk gilsonite approximately 140sx cement down 3:48PM 01/01/83.
17. Describe Proposed or Complete work) SEE RULE 1103.  01/01/83	Ran 175jts. 5½" 17# & 15.5#/', seamless, H-production casing, total 7028.96', set @ 70 Pace-setter Lite w/ 10#/sk salt, ½#/sk cell + 300sx Class "C" neat cement. Circulated to surface. Bumped plug w/ 2500psi. Plug Tested 5½" production casing w/ 1200psi for	40, 8rd thread, ST&C, new 07'. Cemented w/ 1510sx o-seal, 5#/sk gilsonite approximately 140sx cement down 3:48PM 01/01/83.
17. Describe Proposed or Complete work) SEE RULE 1103.  01/01/83	Ran 175jts. 5½" 17# & 15.5#/', seamless, H-production casing, total 7028.96', set @ 70 Pace-setter Lite w/ 10#/sk salt, ½#/sk cell + 300sx Class "C" neat cement. Circulated to surface. Bumped plug w/ 2500psi. Plug Tested 5½" production casing w/ 1200psi for	40, 8rd thread, ST&C, new 07'. Cemented w/ 1510sx o-seal, 5#/sk gilsonite approximately 140sx cement down 3:48PM 01/01/83.
17. Describe Proposed or Complete work) SEE RULE 1103.  01/01/83	Ran 175jts. 5½" 17# & 15.5#/', seamless, H-production casing, total 7028.96', set @ 70 Pace-setter Lite w/ 10#/sk salt, ½#/sk cell + 300sx Class "C" neat cement. Circulated to surface. Bumped plug w/ 2500psi. Plug Tested 5½" production casing w/ 1200psi for	40, 8rd thread, ST&C, new 07'. Cemented w/ 1510sx o-seal, 5#/sk gilsonite approximately 140sx cement down 3:48PM 01/01/83.
17. Describe Proposed or Complete work) SEE RULE 1103.  01/01/83	Ran 175jts. 5½" 17# & 15.5#/', seamless, H-production casing, total 7028.96', set @ 70 Pace-setter Lite w/ 10#/sk salt, ½#/sk cell + 300sx Class "C" neat cement. Circulated to surface. Bumped plug w/ 2500psi. Plug Tested 5½" production casing w/ 1200psi for	40, 8rd thread, ST&C, new 07'. Cemented w/ 1510sx o-seal, 5#/sk gilsonite approximately 140sx cement down 3:48PM 01/01/83.
17. Describe Proposed or Complete work) SEE RULE 1103.  01/01/83	Ran 175jts. 5½" 17# & 15.5#/', seamless, H-production casing, total 7028.96', set @ 70 Pace-setter Lite w/ 10#/sk salt, ½#/sk cell + 300sx Class "C" neat cement. Circulated to surface. Bumped plug w/ 2500psi. Plug Tested 5½" production casing w/ 1200psi for	40, 8rd thread, ST&C, new 07'. Cemented w/ 1510sx o-seal, 5#/sk gilsonite approximately 140sx cement down 3:48PM 01/01/83.
17. Describe Proposed or Complete work) SEE RULE 1103.  01/01/83	Ran 175jts. 5½" 17# & 15.5#/', seamless, H-production casing, total 7028.96', set @ 70 Pace-setter Lite w/ 10#/sk salt, ½#/sk cell + 300sx Class "C" neat cement. Circulated to surface. Bumped plug w/ 2500psi. Plug Tested 5½" production casing w/ 1200psi for	40, 8rd thread, ST&C, new 07'. Cemented w/ 1510sx o-seal, 5#/sk gilsonite approximately 140sx cement down 3:48PM 01/01/83.
17. Describe Proposed or Complete work) SEE RULE 1103.  01/01/83	Ran 175jts. 5½" 17# & 15.5#/', seamless, H-production casing, total 7028.96', set @ 70 Pace-setter Lite w/ 10#/sk salt, ½#/sk cell + 300sx Class "C" neat cement. Circulated to surface. Bumped plug w/ 2500psi. Plug Tested 5½" production casing w/ 1200psi for	40, 8rd thread, ST&C, new 07'. Cemented w/ 1510sx o-seal, 5#/sk gilsonite approximately 140sx cement down 3:48PM 01/01/83.
17. Describe Proposed or Complete work) SEE RULE 1103.  01/01/83	Ran 175jts. 5½" 17# & 15.5#/', seamless, H-production casing, total 7028.96', set @ 70 Pace-setter Lite w/ 10#/sk salt, ½#/sk cell + 300sx Class "C" neat cement. Circulated to surface. Bumped plug w/ 2500psi. Plug Tested 5½" production casing w/ 1200psi for	40, 8rd thread, ST&C, new 07'. Cemented w/ 1510sx o-seal, 5#/sk gilsonite approximately 140sx cement down 3:48PM 01/01/83.
17. Describe Proposed or Complete work) SEE RULE 1103.  01/01/83	Ran 175jts. 5½" 17# & 15.5#/', seamless, H-production casing, total 7028.96', set @ 70 Pace-setter Lite w/ 10#/sk salt, ½#/sk cell + 300sx Class "C" neat cement. Circulated to surface. Bumped plug w/ 2500psi. Plug Tested 5½" production casing w/ 1200psi for	40, 8rd thread, ST&C, new 07'. Cemented w/ 1510sx o-seal, 5#/sk gilsonite approximately 140sx cement down 3:48PM 01/01/83.
17. Describe Proposed or Complete work) SEE RULE 1103.  01/01/83	Ran 175jts. 5½" 17# & 15.5#/', seamless, H-production casing, total 7028.96', set @ 70 Pace-setter Lite w/ 10#/sk salt, ½#/sk cell + 300sx Class "C" neat cement. Circulated to surface. Bumped plug w/ 2500psi. Plug Tested 5½" production casing w/ 1200psi for	40, 8rd thread, ST&C, new 07'. Cemented w/ 1510sx o-seal, 5#/sk gilsonite approximately 140sx cement down 3:48PM 01/01/83.
17. Describe Proposed or Complete work) SEE RULE 1103.  01/01/83	Ran 175jts. 5½" 17# & 15.5#/', seamless, H-production casing, total 7028.96', set @ 70 Pace-setter Lite w/ 10#/sk salt, ½#/sk cell + 300sx Class "C" neat cement. Circulated to surface. Bumped plug w/ 2500psi. Plug Tested 5½" production casing w/ 1200psi for	40, 8rd thread, ST&C, new 07'. Cemented w/ 1510sx o-seal, 5#/sk gilsonite approximately 140sx cement down 3:48PM 01/01/83.
17. Describe Proposed or Complete work) SEE RULE 1103.  01/01/83	Ran 175jts. 5½" 17# & 15.5#/', seamless, H-production casing, total 7028.96', set @ 70 Pace-setter Lite w/ 10#/sk salt, ½#/sk cell + 300sx Class "C" neat cement. Circulated to surface. Bumped plug w/ 2500psi. Plug Tested 5½" production casing w/ 1200psi for	40, 8rd thread, ST&C, new 07'. Cemented w/ 1510sx o-seal, 5#/sk gilsonite approximately 140sx cement down 3:48PM 01/01/83.
17. Describe Proposed or Complete work) SEE RULE 1103.  01/01/83  01/12/83	Ran 175jts. $5\frac{1}{2}$ " 17# & 15.5#/', seamless, H-production casing, total 7028.96', set @ 70 Pace-setter Lite w/ 10#/sk salt, $\frac{1}{4}$ #/sk cell + 300sx Class "C" neat cement. Circulated to surface. Bumped plug w/ 2500psi. Plug Tested $5\frac{1}{2}$ " production casing w/ 1200psi for pressure.	40, 8rd thread, ST&C, new 07'. Cemented w/ 1510sx o-seal, 5#/sk gilsonite approximately 140sx cement down 3:48PM 01/01/83.
17. Describe Proposed or Complete work) SEE RULE 1103.  01/01/83  01/12/83	Ran 175jts. 5½" 17# & 15.5#/', seamless, H-production casing, total 7028.96', set @ 70 Pace-setter Lite w/ 10#/sk salt, ½#/sk cell + 300sx Class "C" neat cement. Circulated to surface. Bumped plug w/ 2500psi. Plug Tested 5½" production casing w/ 1200psi for	40, 8rd thread, ST&C, new 07'. Cemented w/ 1510sx o-seal, 5#/sk gilsonite approximately 140sx cement down 3:48PM 01/01/83.
17. Describe Proposed or Complete work) SEE RULE 1103.  01/01/83  01/12/83	Ran 175jts. $5\frac{1}{2}$ " 17# & 15.5#/', seamless, H-production casing, total 7028.96', set @ 70 Pace-setter Lite w/ 10#/sk salt, $\frac{1}{4}$ #/sk cell + 300sx Class "C" neat cement. Circulated to surface. Bumped plug w/ 2500psi. Plug Tested $5\frac{1}{2}$ " production casing w/ 1200psi for pressure.	40, 8rd thread, ST&C, new 07'. Cemented w/ 1510sx o-seal, 5#/sk gilsonite approximately 140sx cement down 3:48PM 01/01/83.  15 mins., no decline in
17. Describe Proposed or Complete work) SEE RULE 1103.  01/01/83  01/12/83	Ran 175jts. $5\frac{1}{2}$ " 17# & 15.5#/', seamless, H-production casing, total 7028.96', set @ 70 Pace-setter Lite w/ 10#/sk salt, $\frac{1}{4}$ #/sk cell + 300sx Class "C" neat cement. Circulated to surface. Bumped plug w/ 2500psi. Plug Tested $5\frac{1}{2}$ " production casing w/ 1200psi for pressure.	40, 8rd thread, ST&C, new 07'. Cemented w/ 1510sx o-seal, 5#/sk gilsonite approximately 140sx cement down 3:48PM 01/01/83.
17. Describe Proposed or Complete work) SEE RULE 1103.  01/01/83  01/12/83	Ran 175jts. $5\frac{1}{2}$ " 17# & 15.5#/', seamless, H-production casing, total 7028.96', set @ 70 Pace-setter Lite w/ 10#/sk salt, $\frac{1}{4}$ #/sk cell + 300sx Class "C" neat cement. Circulated to surface. Bumped plug w/ 2500psi. Plug Tested $5\frac{1}{2}$ " production casing w/ 1200psi for pressure.	40, 8rd thread, ST&C, new 07'. Cemented w/ 1510sx o-seal, 5#/sk gilsonite approximately 140sx cement down 3:48PM 01/01/83.  15 mins., no decline in
17. Describe Proposed or Complete work) SEE RULE 1103.  01/01/83  01/12/83	Ran 175jts. $5\frac{1}{2}$ " 17# & 15.5#/', seamless, H-production casing, total 7028.96', set @ 70 Pace-setter Lite w/ 10#/sk salt, $\frac{1}{4}$ #/sk cell + 300sx Class "C" neat cement. Circulated to surface. Bumped plug w/ 2500psi. Plug Tested $5\frac{1}{2}$ " production casing w/ 1200psi for pressure.	40, 8rd thread, ST&C, new 07'. Cemented w/ 1510sx o-seal, 5#/sk gilsonite approximately 140sx cement down 3:48PM 01/01/83.  15 mins., no decline in
17. Describe Proposed or Complete work) SEE RULE 1103.  01/01/83  01/12/83	Ran 175jts. 5½" 17# & 15.5#/', seamless, H- production casing, total 7028.96', set @ 70 Pace-setter Lite w/ 10#/sk salt, ¼#/sk cell + 300sx Class "C" neat cement. Circulated to surface. Bumped plug w/ 2500psi. Plug Tested 5½" production casing w/ 1200psi for pressure.  ation above is true and complete to the best of my knowledge and belief.  Agent  Signed By	40, 8rd thread, ST&C, new 07'. Cemented w/ 1510sx o-seal, 5#/sk gilsonite approximately 140sx cement down 3:48PM 01/01/83.  15 mins., no decline in
17. Describe Proposed or Complete work) SEE RULE 1103.  01/01/83  01/12/83  18. I hereby certify that the information of the certific that	Ran 175jts. 5½" 17# & 15.5#/', seamless, H-production casing, total 7028.96', set @ 70 Pace-setter Lite w/ 10#/sk salt, ¼#/sk cell + 300sx Class "C" neat cement. Circulated to surface. Bumped plug w/ 2500psi. Plug Tested 5½" production casing w/ 1200psi for pressure.  atlon above is true and complete to the beat of my knowledge and belief.  And Agent	40, 8rd thread, ST&C, new 07'. Cemented w/ 1510sx o-seal, 5#/sk gilsonite approximately 140sx cement down 3:48PM 01/01/83.  15 mins., no decline in

RECEIVED

JAN 17 1983

O.C.D. HOBBS OFFICE