

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator SHELL WESTERN E&P INC.		8. Farm or Lease Name LIVINGSTON
3. Address of Operator P. O. BOX 991, HOUSTON, TX 77001		9. Well No. 14
4. Location of Well UNIT LETTER <u>M</u> <u>3500</u> FEET FROM THE <u>SOUTH</u> LINE AND <u>367</u> FEET FROM THE <u>WEST</u> LINE, SECTION <u>3</u> TOWNSHIP <u>21-S</u> RANGE <u>37-E</u> NMPM.		10. Field and Pool, or Wildcat BRUNSON FUSSELMAN
15. Elevation (Show whether DF, RT, GR, etc.) 3429' GL		12. County LEA

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data.
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPERATIONS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

4-13-84: Ran 57 jts of 8-5/8" 24# K55 casing set @ 2470', cemented w/1225 sx HOWCO Lite + 15% salt + 1/4#/sx flocele + 200 sx Class "C" cmt + 2% CaCl2. Circulated 250 sx cement. Tested casing w/1150 psi, held OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED A. J. FORE TITLE SUPERVISOR REG. & PERMITTING DATE APRIL 18, 1984

APPROVED BY ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE APR 23 1984

RECEIVED

APR 23 1984

OB
HOBBS OFFICE