

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease  
State ☒ Fee ☐  
5. State Oil & Gas Lease No.  
V-937

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEELEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry Hole	7. Unit Agreement Name
2. Name of Operator Earl M. Craig, Jr. Corp.	8. Farm or Lease Name Enterprise Deep Unit "2"
3. Address of Operator c/o Oil Reports & Gas Services, Inc., Box 763, Hobbs, NM 88241	9. Well No. 1
4. Location of Well UNIT LETTER B 1310 FEET FROM THE North LINE AND 1510 FEET FROM East THE LINE, SECTION 2 TOWNSHIP 21S RANGE 33E NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3785 GR	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOBS ☐  
OTHER Supplemental well History ☐  
ALTERING CASING ☐  
PLUG AND ABANDONMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1105.

Drilled 6 1/8" hole from 11,822 to 14,066. Plugged back to 9915 as follows:

Spotted 36 sacks Class H cement at 13,118  
Spotted 18 sacks Class H cement at 12,912  
Spotted 40 sacks Class H cement at 11,912  
Spotted 40 sacks Class H cement at 10,100

Perforated 9170 to 9410 with 31 holes. Treated with 500 gallons 15% acid.  
Swabbed dry. Plugged for abandonment as follows:

Set cast iron bridge plug at 6100.  
Spotted 20 sacks Class H neat 5812 to 5918  
Spotted 30 sacks Class H neat 5100 to 5200  
Spotted 30 sacks Class C 3392 to 3500  
Spotted 35 sacks Class C 1792 to 1900  
Spotted 35 sacks Class C 466 to 572.  
Set 10 sacks plug at surface with regulation marker.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Donna Heller TITLE Agent DATE 12/14/84

APPROVED BY ORIGINAL SIGNED BY EDDIE SEAY TITLE OIL & GAS INSPECTOR DATE APR 11 1986

CONDITIONS OF APPROVAL, IF ANY: