

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> For <input type="checkbox"/>
5. State Oil & Gas Lease No. A-1375

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
Name of Operator ME-TEX SUPPLY COMPANY
Address of Operator P. O. BOX 2070, HOBBS, NM 88240
Location of Well UNIT LETTER <u>L</u> <u>4290</u> FEET FROM THE <u>South</u> LINE AND <u>990</u> FEET FROM THE <u>West</u> LINE, SECTION <u>3</u> TOWNSHIP <u>21S</u> RANGE <u>36E</u> NMPM.

7. Unit Agreement Name
8. Farm or Lease Name Wallace State
9. Well No. 11
10. Field and Pool, or WHdeat Oil Center Blinbry
12. County Lea

15. Elevation (Show whether DF, RT, GR, etc.)
3531.6' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12/05/84 Spudded 3:30PM.
12/06/84 Ran 32jts. 8 5/8" surface casing, 24#/' , K-55, ST&C, set @ 1308'. Cemented with 560sx Pacemaker Lite w/ 2% CaCl₂ + 200sx Class "C" w/ 2% CaCl₂. Plug down 7:00PM 12/06/84. Circulated 140sx cement. Pressure tested surface casing for 30 minutes @ 1200# - no decline in pressure.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jerry Sexton TITLE Agent DATE 12/07/84
ORIGINAL SIGNED BY JERRY SEXTON
APPROVED BY DISTRICT I SUPERVISOR TITLE _____ DATE DEC 11 1984
SIGNATURES OF APPROVAL, IF ANY: