STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

	40. 01 COPIES OCCEIVES	T		
	DISTRIBUTION			
	SANTA PE			
	FILE			
	U.1.0.1.			
1	LAND OFFICE			
,	OPERATOR	1		

CONDITIONS OF APPROVAL, IF ANYI

OIL CONSERVATION DIVISION

SANTA FE, NEW MEXICO 875Q1	Revised 10-1-7
V.s.a.s. 7341	Sa. Indicate Type of Lease
LAND OFFICE	State X F↔
" OPERATOR	5, State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS	
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	
WELL X , SAB OTHER-	Eunice Monument South L
Chevron U.S.A. Inc.	8, Form of Lease Hame
Address of Operator	9. Well No.
P.O. Box 670 Hobbs, NM 88240	328
UNIT LETTER J 2080 FEET FROM THE South LINE AND 1880 FEET FI	Eunice Monument
THE LAST LINE, SECTION 7 TOWNSHIP 21S RANGE 36E	~.(.
15. Elevation (Show whether DF, RT, GR, etc.) 3584.3 GL	12. County
	Lea
Check Appropriate Box To Indicate Nature of Notice, Report or NOTICE OF INTENTION TO:	Other Data ENT REPORT OF:
	_
FMERARALLY ARABON THE REMEDIAL WORK	ALTERING CASING
COMMENCE ORILLING OPHS. CHANGE PLANS CASING TEST AND CEMENT JOS X	PLUS AND ASANDONMENT
OTHER	
OTHER	
Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, includ	ing estimated date of starting any propose
	•
TD 11" hole @ 2751' 1:00 AM 3-25-1986. RU and ran 18 joints 8 5/8 and 48 joints 8 5/8" 24# K-55 casing set @ 2757'. Cemented with	8" 32# K-55 ST&C
"C" with 16% Gel 2% Salt .2% HR-7 and 200 sacks class "C" Neat.	Plua down 9:00 AM
3-25-1986. Circulated 154 sacks to surface. Tested casing to 100	00 psi for 30 minutes
(UK). Total WOC before drill out 13 hours. (Compressive Strength	n of cement in 12
hours = 1300 psi.	
•	
hereby certify that the information above is true and complete to the best of my knowledge and belief.	
WHRII 1	2.07.4000
. D. Leagh. virus Division Drilling Mana	ger bate 3-27-1986
ORIGINAL SIGNED BY JERRY SEXTON	MAR 3 1 1986
DISTRICT I SUPERVISOR TITLE	and the Late of the Part of the Control of the Cont