

OIL CONSERVATION DIVISION
P. O. BOX 2038
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Free ☐
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input checked="" type="checkbox"/>	GAS WELL <input type="checkbox"/>	OTHER <input type="checkbox"/>	7. Unit Agreement Name Eunice Monument South Ut
Name of Operator Chevron U.S.A. Inc.			8. Farm or Lease Name
Address of Operator P.O. Box 670, Hobbs, NM 88240			9. Well No. 194
Location of Well UNIT LETTER <u>G</u> . <u>2254</u> FEET FROM THE <u>North</u> LINE AND <u>2080</u> FEET FROM THE <u>East</u> LINE, SECTION <u>6</u> TOWNSHIP <u>21S</u> RANGE <u>36E</u> NMPM.			10. Field and Pool, or WHcat Eunice Monument G/SA
15. Elevation (Show whether DF, RT, GR, etc.) 3558			12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
ILL OR ALTER CASING <input type="checkbox"/>	OTHER <u>add perfs, acidz, rtn to prod.</u> <input checked="" type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

It is proposed to knock out CIBP at 3930' and chase same to PBTD 4150, perforate the 5 1/2" csg w/4" guns 1 SPF and 180° phasing (every other foot) at 3774-87, 3799-3810, 3817-23, 3828-44, 3851-64, and 4084-4096. (71 holes).
Run GR/CCL to PBTD, acidz with 15% NEFE HCL, flush to bottom perfs. Swab, squeeze procedure will be based on swab test results (if zone 5 water), set pkr at 3880', spot acid across perfs 3774-3864, follow spot acid w/ 4500 gal 15% NEFE HCL dropping 90 l.l RCNB's in the first 4000 gal of acid, flush to bottom perf. Swab, TIH w/ production equipment. Turn over to production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

by M. E. Akim

TITLE Staff Drilling Engineer

DATE Dec. 28, 1988

ORIGINAL SIGNED BY JERRY SEXTON

DISTRICT I SUPERVISOR

TITLE

DATE DEC 29 1987

COPIES OF APPROVAL, IF ANY: