Form 3150-5 (November 1983) (Formerly 9-331) DEPARTMEN. OF THE INTERIOR (Other Instructions re- BUREAU OF LAND MANAGEMENT	Form approved. Budget Bureau No. 1004-0135 Expires August 31, 1985 5. Lease Designation and Serial No. LC-031740-A
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
OTL GAS GAS COTHER	7. UNIT AGREEMENT NAME Eunice Monument South Unit
2. NAME OF OPERATOR	8. FARM OR LEASE NAME
Chevron U.S.A. Inc.	9. WELL NO.
P.O. Box 670, Hobbs, New Mexico 88240	375
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface	10. FIELD AND FOOL, OR WILDCAT Eunice Monument G/SA
2130	11. SEC., T., R., M., OR REK. AND SURVEY OR AREA
Unit G, 2310' FNL & 1780' FEL	Sec. 18, T21S, R36E .
14. PERMIT NO. 15. ELEVATIONS (Show whether DF. ET. CR. etc.) 3647.6 GL	12. COUNTY OF PARISH 13. STATE Lea NM
16. Check Appropriate Box To Indicate Nature of Notice, Report, or O	ther Data
	INT REPORT OF:
TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF FRACTURE TREAT MULTIPLE COMPLETE	REPAIRING WELL
SHOOT OR ACIDIZE ABANDON® SHOOTING OR ACIDIZING	. ALTERING CASING
REPAIR WELL CHANGE PLANS (Other) Completion (
(Other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, in proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical ment to this work.)	of multiple completion on Well tion Report and Log form.)
Drilled FC out at 4243', drld cmt to 4298' perf 4294' - 96 (2 Acdz perfs w/600 gal 15% NEFE HCL, dropped 3 1.1 SG RCNBs, swat ret at 4259, squeezed off perfs 4294-96, Perf 4193-4223' 1 JHPF Acdzd w/2500 gal 15% NEFE HCL, dropped 45 1.1 SG RCNBs, swab te retainer at 4175' squeezed off perfs 4193' 4223 w/250 sx cmt. 120 deg ph. (42 holes) Acdzd perfs w/3100 gal 15% NEFE HCL, droswab tested perfs, perf 3990-4028,1 JHPF,120 deg phas. (38 hol JHPF, 180 deg phas, (32 holes), 3855 - 3884, 1 JHPF, 180 ph, holes, Did not treat perfs, Equip for pump: Ran Baker 5 1/2" A std 2 7/8" SN, 128 jts 6.5# J-55 EUE 8rd tbg, set pkr b/t zone (w,17.0'KB), Ran 2 1/2" x 2" x 20' pump, 2' x 2/3" sub, 106 - 3 rods, 8' x 7/8" sub, 6' x 7/8" sub, 4' x 7/8" sub. Work comp	OHPF at 180 deg (4 holes) of tested perfs, set cmt at 0 ph (30 holes) ested perfs, Set cmt Perf 4074 - 4156 1 JHPF opped 63 1.1 SG RCNBs les), 3908 - 3940', (29 holes), Total 99 As lockst pkr, X-0, es 3 & 4 at 4052', 374" rods, 53 - 7/8"
ACCEPTED FOR	RECORD
JUL 10	1987
	JS
CARLSBAD, NEV	•
18. I hereby certify that the foregoing is true and correct SIGNED	DATE JUNE 27, 1987
(This space for Federal or State office use)	
APPROVED BY TITLE TITLE	DATE

and the same of th

WILL TO SHALL STATES