

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

50025-30281
Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985
5. LEASE DESIGNATION AND SERIAL NO.
LC-031740-A

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Injector	7. UNIT AGREEMENT NAME Eunice Monument South
2. NAME OF OPERATOR Chevron U.S.A. Inc.	8. FARM OR LEASE NAME Unit
3. ADDRESS OF OPERATOR P.O. Box 670, Hobbs, New Mexico 88240	9. WELL NO. 410
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FEL and 1860' FSL	10. FIELD AND POOL, OR WILDCAT Eunice Monument G/SA
14. PERMIT NO.	11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA Sec. 18, T21S, R36E
15. ELEVATIONS (Show whether OF, AT, OR, ETC.) 3629.9	12. COUNTY OR PARISH Lea
	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETION ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☒ CSG	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spud 12 1/4" hole at 6:30pm 3-27-88. TD 12 1/4" hole at 11:30pm 3-28-88. Circulate and condition hole to run casing. Run 8 5/8" 24#, K-55, ST&C. Set at 1385'. FC at 1309'. Circulate casing capacity. Cement w/900sx Class C. Displace w/83 bbls BW. Plug down at 9:45am. 3-29-88. Circ 250sx to surface. Bump plug w/1000psi. WOC (33 1/2 hrs). Cut off csg and weld on wellhead. Test weld to 950psi for 15 min. OK. National 10" to 3000psi.

18. I hereby certify that the foregoing is true and correct

SIGNED M. E. Albarrin TITLE Staff Drlg. Engr. DATE April 26, 1988

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ ACCEPTED FOR RECORD
CONDITIONS OF APPROVAL, IF ANY: _____ DATE _____

MAY 11 1988

*See Instructions on Reverse Side

SJS
CARLSBAD, NEW MEXICO

RECEIVED

MAY 16 1988

OCD
NOBBS OFFICE