

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

30-025-30664
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		3. LEASE DESIGNATION AND SERIAL NO. NM63020
2. NAME OF OPERATOR Santa Fe Energy Operating Partners, L.P.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR 500 W. Illinois, Suite 500, Midland, TX 79701		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface Unit K 1980' FSL & 1980' FWL, Sec. 28, T-21S, R-32E		8. FARM OR LEASE NAME Bilbrey 28A Federal
14. PERMIT NO. API #30-025-30664		9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3682.7' GR		10. FIELD AND POOL, OR WILDCAT Und. Bilbrey Morrow
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 28, T-21S, R-32E
		12. COUNTY OR PARISH Lea
		13. STATE NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>	WATER SHUT-OFF	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	FRACTURE TREATMENT	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	SHOOTING OR ACIDIZING	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	(Other) Set csg string	<input checked="" type="checkbox"/>
(Other)	<input type="checkbox"/>	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

10-09-89: Depth 4650'. Ran 108 jts 9 5/8" 40# K-55 ST&C csg and set at 4650'. Cemented w/3400 sx Howco lite w/15#/sk salt & 1/4#/sk flocele. Tail w/200 sx Premium plus containing 2% CaCl₂. PD at 4:00 PM CST. Circ 50 sx cmt to pit. WOC 18 hrs. Pour pea gravel and concrete in 13 3/8" csg and cellar to 9 5/8" base plate. Tested csg to 1500 psi for 30 min - okay. Resume drilling operations.

RECEIVED
OCT 15 9 40 AM '89
CARLSBAD
AREA

18. I hereby certify that the foregoing is true and correct.

SIGNED Jerry Mc Cullough TITLE Sr. Prod. Clerk DATE 10-12-89

(This space for Federal or State office use)

APPROVED BY (ORIG. SGD.) DAVID R. GLASS TITLE DATE

CONDITIONS OF APPROVAL, IF ANY:

CARLSBAD, NEW MEXICO

*See Instructions on Reverse Side