Submit 3 Copies

CONDITIONS OF APPROVAL, IF ANY:

State of New Mexico Energy, Minerals and Natural Resources Department

F	orm	C-	100	3
P	evia	d :	1-1	-89

District Office	LANGS, MIRAMO MRI MANIME IN	sources Department		Revised 1-1-89	
DISTRICT I P.O. Box 1980, Hobbs, NM 88240 DISTRICT II P.O. Drawer DD, Artesia, NM 88210 OIL CONSERVATION DIVISION P.O. Box 2088 Santa Fe, New Mexico 87504-2088			WELL API NO. 30-025-30886 5. Indicate Type of Lease		
1000 Rio Brazos Rd., Aztec, NM 87410			6. State Oil & Ga	a Lease No.	
	ICES AND REPORTS ON WEL				
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"			7. Lease Name or Unit Agreement Name		
(FORM C	-101) FOR SUCH PROPOSALS.)		BILBREY -32-	- STATE COM	
OR OAS WELL X	OTHER				
2. Name of Operator TEXACO PRODUCING INC.	, , , , , , , , , , , , , , , , , , , 		8. Well No.		
3. Address of Operator			9. Pool name or V	Wildcat	
	lland, Texas 79702		BILBREY MOR	ROW, BILBREY ATOKA	
4. Well Location F 19	80 Feet From The NORTH	7.5	1990	- WEST	
Unit Letter :	Pet Prom The TOTAL	Line and	1900 Feet From	The WEST	
Section 32	Township 21-SOUTH Ra	nge 32-EAST	NMPM LEA	Coun	
	10. Elevation (Show whether GR-3742', KB-3767'				
11. Check	Appropriate Box to Indicate I		eport or Other		
NOTICE OF INT			SEQUENT F		
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK			
				ALTERING CASING	
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING		PLUG AND ABANDONMEN	
PULL OR ALTER CASING		CASING TEST AND CE	EMENT JOB		
OTHER:		OTHER:			
 Describe Proposed or Completed Opers work) SEE RULE 1103. DRILL 8 3/4 HOLE TO 1200 CAL-BHC-SONIC FROM 11998' RAN 53 JTS OF 7, 29#, P-DV TOOL @ 8999'. HALLIBURTON CEMENTED 18 F/B 200 SX CLASS H w/ 0.2% SALT & 1/4# FLOCELE @ 12.8 	0'. TD @ 4:45pm 6-19-90. C TO 4600'. 110, LT&C (2285') & 179 JTS ST STAGE: 300 SX 35/65 POZ HR-7 @ 15.6ppg. CIRC 45 SX ppg. CLOSE DV @ 4:30pm 6-2	OMPUTALOG RAN GR OF 7, 26#, P-110 CLASS H w/ 6% GE (. 2nd STAGE: 1500 22-90. RAN TEMP S	-CAL-CNL-LDT LT&C (7912') L, 5% SALT & 6 SX 35/65 POZ	Γ, GR-CAL-DIL & GR- CSG. SET AT 12000'. 0.3% HR-4 @ 12.8ppg. Z CLASS H w/ 6%GEL,	
4. INSTALL WELLHEAD. J&W 15. WOC TIME 34 HRS FROM 4: 6. DRILL CEMENT AND DV TOO 7. TEST CSG. TO 5000# FOR 38. DRILL SHOE AND 7' OF FOR 9. DRILLING 6 1/8 HOLE.	30pm 6-22-90 TO 2:30am 6- L. DRILL CEMENT FROM 1138! 10 MIN. FROM 2:45 TO 3:15an	-24-90. 5' TO 11970'. n 6-25-90.			
					
I hereby certify that the information above is tru	1/				
SIGNATURE W2	т	DRILLING SUPERIN	(I E.NDENT	DATE 06-26-90	
TYPEORPRINTNAME C. P. BASHAM				TELEPHONE NO. 915-68	
(This space for State Use) ORIGINAL SIGNED DISTRICT I S					
URIGINAL SIGNED	BY JERRY SEXTON			JUN 29 19	
APPROVED BY DISTRICT IS	UPERVISO2 III	ue		DATE	
