

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

| |
|---|
| WELL API NO. 30-025-30886 |
| 5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/> |
| 6. State Oil & Gas Lease No. LG 6640 |
| 7. Lease Name or Unit Agreement Name BILBREY -32- STATE COM |
| 8. Well No. 1 |
| 9. Pool name or Wildcat BILBREY MORROW, BILBREY ATOKA |
| 10. Elevation (Show whether DF, RKB, RT, GR, etc.) GR-3742', KB-3767' |

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

| | |
|--|--|
| 1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER | 2. Name of Operator TEXACO PRODUCING INC. |
| 3. Address of Operator P. O. Box 3109 Midland, Texas 79702 | 4. Well Location Unit Letter F : 1980 Feet From The NORTH Line and 1980 Feet From The WEST Line Section 32 Township 21-SOUTH Range 32-EAST NMPM LEA County |
| 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data | |

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. BASIN #16 SPUD 17 1/2 HOLE AT 7:00am 5-23-90. DRILL TO 1150'. TD AT 1:00am 5-25-90.
2. RAN 27 JTS OF 13 3/8, 54.5#, K-55, ST&C CSG. SET AT 1150'. 10 CENTRALIZERS.
3. HALLIBURTON CEMENTED w/ 950 SX CLASS H w/ 2% GEL & 2% CaCl2 @ 14.8ppg. F/B 200 SX CLASS H @ 15.6ppg. PLUG DOWN AT 5:00pm 5-25-90. DID NOT CIRC. RAN TEMP. SURVEY. TOC AT 100'. RAN 1 in. TUBING & CEMENTED TO SURFACE WITH 250 SX CLASS @ 15.6ppg.
4. J&W TESTED HEAD TO 550#. NU BOP AND TEST TO 3000#.
5. WOC TIME 29 1/4 HOURS FROM 5:00pm 5-25-90 TO 9:15pm 5-26-90.
6. TESTED CASING TO 1000# FOR 30 MIN FROM 12:15am TO 12:45am 5-27-90.
7. DRILLING 12 1/4 HOLE.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE C. P. Basham TITLE DRILLING SUPERINTENDENT DATE 05-29-900

TYPE OR PRINT NAME C. P. BASHAM

TELEPHONE NO. 915-6884606

(This space for State Use)

Orig. Sign
Paul Kautz
Geologist

JUN 9 4 1990

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: