Submit 5 Copies to Appropriate District Office	State of New Mexico Energy, . erals and Natural Resources Department		Form C-103 Revised 1-1-89			
DISTRICT I P.O. Box 1980, Hobbs, NM 88240 OIL CONSERVATION DIVISION P.O. Box 2088			Well API NO. 30-025-31117			
ISTRICT II Santa Fe, New Mexico 87504-2088 O. Drawer DD, Artesia, NM 88210			5. Indicate Type of Lease STATE XX FEE			
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410	6. State Oil & Gas Lease No.					
SUNDRY NOT (DO NOT USE THIS FORM FOR PRO DIFFERENT RESEN (FORM C	7. Lease Name or Unit Agreement Name					
1. Type of Well: OIL WELL GAS WELL X	OTHER		State "A" Com			
2. Name of Operator		8. Well No.				
Doyle Hartman 3. Address of Operator P. O. box 10426, Mic		9. Pool name or Wildcat Eumont (Y-7R-Qn) Pro Gas				
4. Well Location Unit Letter :1	650 Feet From The South	Line and845	Feet From The Line			
Section 5 Township 21-S Range 36-E NMPM Lea County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3586, 2 GR 3586, 2 GR 000000000000000000000000000000000000						
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:						
		COMMENCE DRILLING OPNS.				
PULL OR ALTER CASING	ULL OR ALTER CASING					
OTHER:						

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well at 5:00 PM CST 1-5-91. Drilled 12-1/4" hole to a total depth of 497'. Circulated hole for 3/4 hour. Pulled out of hole with drill string. Ran 1 jt. 9-5/8" OD 36 lb/ft, K-55, LT&C casing, 2 jts. 9-5/8" OD 36 lb/ft. K-55 LT&C casing, 8 jts. 9-5/8" OD 36 lb/ft. K-55 ST&C casing, 1 Weatherford 9-5/8" Texas Pattern notched shoe, and 1 Weatherford 9-5/8" superseal float collar. and 6 centralizers (total of 475.54' of casing). Landed casing at 494'. Cemented casing with 375 sx of API Class-C cement containing 2% CaCl2. Circulated 140 sx of excess cement to pit. Plug down at 4:30 AM CST 1-6-91. Pressured casing to 1500 psi. Released pressure and float held okay. WOC 18 hours.

	•	ompice to the best of my knowl	TTLE	Engineer	DATE 1-10-91
TYPE OR PRINT NAME	Michael				ТЕLЕРНЮМЕ NO. 915/684-401
(This space for State Use) OF CAREAR STATES AND STATES					
APPROVED BY			TITLE		DATE