

30-025-31518

Form M60-5
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Collins & Ware, Inc.

3. Address and Telephone No.

303 W. Wall, Suite 2200, Midland, Texas 79701

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FSL & 1980' FEL Sec. 18, T-21-S, R-32-E

5. Lease Designation and Serial No.

NM 14328

6. If Indian, Allottee or Tribe Name

7. If Unit or C.A. Agreement Designation

8. Well Name and No.

N.L. Federal NL

9. API Well No.

2

10. Field and Pool, or Exploratory Area

Indes, Livingston Ridge, Delawa

11. County or Parish, State

Lea

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other Spud and Surface

Casing (13-3/8")

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Zia Drill spudded a seventeen and one-half inch hole at 1:30 PM June 10, 1992. The seventeen and one-half inch hole was drilled to a depth of 822' K.B. Thirteen and three-eighths 61#/ft., K-55, ST&C casing was run and set at 822.50' K.B. Cemented with 850 sacks Premium Plus cement with 2% CACL2. Plug down at 5:15 PM June 11, 1992. Circulated 250 sacks cement to surface. Cementing witnessed by Pat Hutching with the 3LM. Waited on cement for 24 hours. Tested Blind rams to 2000 psig. Tested pipe rams and choke manifold to 2000 psig with rig pump.

EO FOR RECORD

JUL 13 1992

NEW MEXICO

14. I hereby certify that the foregoing is true and correct

Signed

Samie F. Brown

Title Agent for Collins & Ware, Inc.

Date 6/16/92

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any: